



Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	64.5 °	65.0 °	65.0 °	65.0 °
B	head tube length	4.7 in	4.9 in	5.3 in	5.7 in
C	top tube horizontal	22.8 in	23.4 in	24.6 in	25.8 in
D	standover height	30.2 in	30.2 in	30.2 in	30.2 in
E	BB offset	-1.2 in	-1.2 in	-1.2 in	-1.2 in
F	BB height	13.7 in	13.7 in	13.7 in	13.7 in
G	wheel base	48.1 in	48.5 in	49.8 in	51.0 in
H	BB center to toptube center				
I	BB center to top of seattube	16.2 in	17.3 in	18.5 in	19.7 in
J	seat angle	77.0 °	76.9 °	76.9 °	76.8 °
K	chainstay	17.9 in	17.9 in	17.9 in	17.9 in
L	reach	17.0 in	17.6 in	18.6 in	19.7 in
M	stack	25.0 in	25.3 in	25.6 in	26.0 in
N	stem length	2.0 in	2.0 in	2.4 in	2.4 in
O	trail	5.2 in	5.1 in	5.1 in	5.1 in
P	Fork length	22.3 in	22.3 in	22.3 in	22.3 in
Q	Maximum Seatpost Insertion	9.6 in	10.4 in	11.8 in	12.6 in
R	Crank Length	6.5 in	6.5 in	6.5 in	6.5 in

Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	64.5 °	65.0 °	65.0 °	65.0 °
B	head tube length	4.7 in	4.9 in	5.3 in	5.7 in
C	top tube horizontal	22.8 in	23.4 in	24.6 in	25.8 in
D	standover height	30.2 in	30.2 in	30.2 in	30.2 in
E	BB offset	-1.2 in	-1.2 in	-1.2 in	-1.2 in
F	BB height	13.7 in	13.7 in	13.7 in	13.7 in
G	wheel base	48.1 in	48.5 in	49.8 in	51.0 in
H	BB center to toptube center				
I	BB center to top of seattube	16.2 in	17.3 in	18.5 in	19.7 in
J	seat angle	77.0 °	76.9 °	76.9 °	76.8 °
K	chainstay	17.9 in	17.9 in	17.9 in	17.9 in

L	reach	17.0 in	17.6 in	18.6 in	19.7 in
M	stack	25.0 in	25.3 in	25.6 in	26.0 in
N	stem length	2.0 in	2.0 in	2.4 in	2.4 in
O	trail	5.2 in	5.1 in	5.1 in	5.1 in
P	Fork length	22.3 in	22.3 in	22.3 in	22.3 in
Q	Maximum Seatpost Insertion	9.6 in	10.4 in	11.8 in	12.6 in
R	Crank Length	6.5 in	6.5 in	6.5 in	6.5 in