



### Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	63.8 °	64.4 °	64.4 °	64.4 °
B	head tube length	4.7 in	4.9 in	5.3 in	5.7 in
C	top tube horizontal	22.8 in	23.4 in	24.6 in	25.8 in
D	standover height	30.4 in	30.4 in	30.4 in	30.4 in
E	BB offset	-1.0 in	-1.0 in	-1.0 in	-1.0 in
F	BB height	13.9 in	13.9 in	13.9 in	13.9 in
G	wheel base	48.5 in	48.8 in	50.1 in	51.4 in
H	BB center to toptube center				
I	BB center to top of seattube	16.1 in	18.5 in	18.5 in	19.7 in
J	seat angle	76.3 °	76.3 °	76.2 °	76.2 °
K	chainstay	17.9 in	17.9 in	17.9 in	17.9 in
L	reach	16.7 in	17.3 in	18.4 in	19.4 in
M	stack	25.2 in	25.5 in	25.8 in	26.2 in
N	stem length	2.0 in	2.0 in	2.4 in	2.4 in
O	trail	5.3 in	5.2 in	5.2 in	5.2 in
P	Fork length	23.0 in	23.0 in	23.0 in	23.0 in
Q	Maximum Seatpost Insertion	9.6 in	10.4 in	11.8 in	12.6 in
R	Crank Length	6.5 in	6.5 in	6.5 in	6.5 in

### Geometry Chart (MM)

		S	M	L	XL
A	head tube angle	63.8 °	64.4 °	64.4 °	64.4 °
B	head tube length	120.0 mm	125.0 mm	135.0 mm	145.0 mm
C	top tube horizontal	579.4 mm	595.0 mm	625.6 mm	656.4 mm
D	standover height	772.3 mm	772.3 mm	772.3 mm	772.3 mm
E	BB offset	-25.0 mm	-25.0 mm	-25.0 mm	-25.0 mm
F	BB height	352.0 mm	352.0 mm	352.0 mm	352.0 mm
G	wheel base	1,230.8 mm	1,240.6 mm	1,272.6 mm	1,304.4 mm
H	BB center to toptube center				
I	BB center to top of seattube	410.0 mm	470.0 mm	470.0 mm	500.0 mm
J	seat angle	76.3 °	76.3 °	76.2 °	76.2 °
K	chainstay	454.0 mm	454.0 mm	454.0 mm	454.0 mm

L	reach	425.4 mm	438.4 mm	466.3 mm	493.9 mm
M	stack	639.7 mm	647.3 mm	656.5 mm	665.8 mm
N	stem length	50.0 mm	50.0 mm	60.0 mm	60.0 mm
O	trail	135.4 mm	131.6 mm	131.4 mm	131.3 mm
P	Fork length	583.7 mm	583.7 mm	583.7 mm	583.7 mm
Q	Maximum Seatpost Insertion	245.0 mm	265.0 mm	300.0 mm	320.0 mm
R	Crank Length	165.0 mm	165.0 mm	165.0 mm	165.0 mm