



### Geometry Chart (INCHES)

|   |                              | S / 900 | M / 900 | L / 900 | XL / 900 | XXL     |
|---|------------------------------|---------|---------|---------|----------|---------|
| A | head tube angle              | 67.4 °  | 67.4 °  | 67.4 °  | 67.4 °   | 67.4 °  |
| B | head tube length             | 3.5 in  | 3.9 in  | 4.3 in  | 4.7 in   | 4.7 in  |
| C | top tube horizontal          | 22.8 in | 23.8 in | 24.8 in | 26.0 in  | 26.8 in |
| D | standover height             | 29.7 in | 30.9 in | 31.7 in | 32.9 in  | 34.3 in |
| E | BB offset                    | -2.4 in | -2.4 in | -2.4 in | -2.4 in  | -2.4 in |
| F | BB height                    | 12.4 in | 12.4 in | 12.4 in | 12.4 in  | 12.4 in |
| G | wheel base                   | 43.8 in | 44.8 in | 45.8 in | 47.1 in  | 47.9 in |
| H | BB center to toptube center  |         |         |         |          |         |
| I | BB center to top of seattube | 15.4 in | 17.3 in | 18.9 in | 20.9 in  | 22.8 in |
| J | seat angle                   | 75.0 °  | 75.0 °  | 75.0 °  | 75.0 °   | 75.0 °  |
| K | chainstay                    | 16.7 in | 16.7 in | 16.7 in | 16.7 in  | 16.7 in |
| L | reach                        | 16.5 in | 17.4 in | 18.2 in | 19.4 in  | 20.2 in |
| M | stack                        | 23.5 in | 23.8 in | 24.2 in | 24.6 in  | 24.6 in |
| N | stem length                  | 2.0 in  | 2.4 in  | 2.8 in  | 3.1 in   | 3.1 in  |
| O | trail                        | 4.4 in  | 4.4 in  | 4.4 in  | 4.4 in   | 4.4 in  |

### Geometry Chart (MM)

|   |                              | S / 900    | M / 900    | L / 900    | XL / 900   | XXL        |
|---|------------------------------|------------|------------|------------|------------|------------|
| A | head tube angle              | 67.4 °     | 67.4 °     | 67.4 °     | 67.4 °     | 67.4 °     |
| B | head tube length             | 90.0 mm    | 100.0 mm   | 110.0 mm   | 120.0 mm   | 120.0 mm   |
| C | top tube horizontal          | 580.0 mm   | 605.0 mm   | 630.0 mm   | 660.0 mm   | 680.0 mm   |
| D | standover height             | 755.0 mm   | 786.0 mm   | 805.0 mm   | 835.0 mm   | 870.0 mm   |
| E | BB offset                    | -60.0 mm   | -60.0 mm   | -60.0 mm   | -60.0 mm   | -60.0 mm   |
| F | BB height                    | 315.0 mm   | 315.0 mm   | 315.0 mm   | 315.0 mm   | 315.0 mm   |
| G | wheel base                   | 1,111.8 mm | 1,138.2 mm | 1,164.6 mm | 1,195.9 mm | 1,215.9 mm |
| H | BB center to toptube center  |            |            |            |            |            |
| I | BB center to top of seattube | 390.0 mm   | 440.0 mm   | 480.0 mm   | 530.0 mm   | 580.0 mm   |
| J | seat angle                   | 75.0 °     | 75.0 °     | 75.0 °     | 75.0 °     | 75.0 °     |
| K | chainstay                    | 425.0 mm   | 425.0 mm   | 425.0 mm   | 425.0 mm   | 425.0 mm   |
| L | reach                        | 420.3 mm   | 442.8 mm   | 463.3 mm   | 492.9 mm   | 512.9 mm   |
| M | stack                        | 596.1 mm   | 605.3 mm   | 614.6 mm   | 623.8 mm   | 623.8 mm   |
| N | stem length                  | 50.0 mm    | 60.0 mm    | 70.0 mm    | 80.0 mm    | 80.0 mm    |

