



Geometry Chart (INCHES)

		S / 900	M / 900	L / 900	XL / 900	XXL
A	head tube angle	67.4 °	67.4 °	67.4 °	67.4 °	67.4 °
B	head tube length	3.5 in	3.9 in	4.3 in	4.7 in	4.7 in
C	top tube horizontal	22.8 in	23.8 in	24.8 in	26.0 in	26.8 in
D	standover height	29.7 in	30.9 in	31.7 in	32.9 in	34.3 in
E	BB offset	-2.4 in	-2.4 in	-2.4 in	-2.4 in	-2.4 in
F	BB height	12.4 in	12.4 in	12.4 in	12.4 in	12.4 in
G	wheel base	43.8 in	44.8 in	45.8 in	47.1 in	47.9 in
H	BB center to toptube center					
I	BB center to top of seattube	15.4 in	17.3 in	18.9 in	20.9 in	22.8 in
J	seat angle	75.0 °	75.0 °	75.0 °	75.0 °	75.0 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	16.5 in	17.4 in	18.2 in	19.4 in	20.2 in
M	stack	23.5 in	23.8 in	24.2 in	24.6 in	24.6 in
N	stem length	2.0 in	2.4 in	2.8 in	3.1 in	3.1 in
O	trail	4.4 in	4.4 in	4.4 in	4.4 in	4.4 in

Geometry Chart (INCHES)

		S / 900	M / 900	L / 900	XL / 900	XXL
A	head tube angle	67.4 °	67.4 °	67.4 °	67.4 °	67.4 °
B	head tube length	3.5 in	3.9 in	4.3 in	4.7 in	4.7 in
C	top tube horizontal	22.8 in	23.8 in	24.8 in	26.0 in	26.8 in
D	standover height	29.7 in	30.9 in	31.7 in	32.9 in	34.3 in
E	BB offset	-2.4 in	-2.4 in	-2.4 in	-2.4 in	-2.4 in
F	BB height	12.4 in	12.4 in	12.4 in	12.4 in	12.4 in
G	wheel base	43.8 in	44.8 in	45.8 in	47.1 in	47.9 in
H	BB center to toptube center					
I	BB center to top of seattube	15.4 in	17.3 in	18.9 in	20.9 in	22.8 in
J	seat angle	75.0 °	75.0 °	75.0 °	75.0 °	75.0 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	16.5 in	17.4 in	18.2 in	19.4 in	20.2 in
M	stack	23.5 in	23.8 in	24.2 in	24.6 in	24.6 in
N	stem length	2.0 in	2.4 in	2.8 in	3.1 in	3.1 in

