



### Geometry Chart (INCHES)

		S / 900	M / 900	L / 900	XL / 900
A	Head tube angle (+0.6° Headset Setting)	67.9 °	67.9 °	67.9 °	67.9 °
B	head tube length	3.5 in	3.7 in	4.3 in	4.7 in
C	top tube horizontal	22.6 in	23.6 in	24.6 in	25.8 in
D	standover height	29.6 in	30.7 in	31.5 in	32.9 in
E	BB offset	-2.4 in	-2.4 in	-2.4 in	-2.4 in
F	BB height	12.3 in	12.3 in	12.3 in	12.3 in
G	wheel base	43.5 in	44.5 in	45.6 in	46.8 in
H	BB center to toptube center				
I	BB center to top of seattube	15.4 in	17.3 in	18.9 in	20.9 in
J	seat angle	75.4 °	75.4 °	75.3 °	75.3 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	16.5 in	17.4 in	18.3 in	19.3 in
M	stack	23.6 in	23.8 in	24.4 in	24.7 in
N	stem length	2.0 in	2.4 in	2.8 in	3.1 in
O	trail	4.1 in	4.1 in	4.1 in	4.1 in

### Geometry Chart (INCHES)

		S / 900	M / 900	L / 900	XL / 900
A	Head tube angle (+0.6° Headset Setting)	67.9 °	67.9 °	67.9 °	67.9 °
B	head tube length	3.5 in	3.7 in	4.3 in	4.7 in
C	top tube horizontal	22.6 in	23.6 in	24.6 in	25.8 in
D	standover height	29.6 in	30.7 in	31.5 in	32.9 in
E	BB offset	-2.4 in	-2.4 in	-2.4 in	-2.4 in
F	BB height	12.3 in	12.3 in	12.3 in	12.3 in
G	wheel base	43.5 in	44.5 in	45.6 in	46.8 in
H	BB center to toptube center				
I	BB center to top of seattube	15.4 in	17.3 in	18.9 in	20.9 in
J	seat angle	75.4 °	75.4 °	75.3 °	75.3 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	16.5 in	17.4 in	18.3 in	19.3 in
M	stack	23.6 in	23.8 in	24.4 in	24.7 in
N	stem length	2.0 in	2.4 in	2.8 in	3.1 in

