



Geometry Chart (INCHES)

		XS/49	S/52	M/54	L/56	XL/58
A	head tube angle	69.5 °	70.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	3.3 in	4.3 in	5.0 in	6.1 in	6.9 in
C	top tube horizontal	20.4 in	21.0 in	21.8 in	22.8 in	23.3 in
D	standover height	29.9 in	30.9 in	31.6 in	32.4 in	33.1 in
E	BB offset	3.0 in	3.0 in	3.0 in	3.0 in	3.0 in
F	BB height	11.6 in	11.6 in	11.6 in	11.6 in	11.6 in
G	wheel base	40.2 in	40.6 in	40.8 in	41.6 in	42.2 in
H	BB center to toptube center					
I	BB center to top of seattube	18.8 in	20.0 in	20.7 in	21.5 in	22.3 in
J	seat angle	74.5 °	74.0 °	73.5 °	73.0 °	73.0 °
K	chainstay	17.1 in	17.1 in	17.1 in	17.1 in	17.1 in
L	reach	14.7 in	14.9 in	15.2 in	15.7 in	16.0 in
M	stack	20.4 in	21.4 in	22.3 in	23.2 in	24.0 in
N	stem length	3.1 in	3.5 in	3.9 in	3.9 in	4.3 in
O	trail	3.2 in	3.0 in	2.8 in	2.8 in	2.8 in

Geometry Chart (MM)

		XS/49	S/52	M/54	L/56	XL/58
A	head tube angle	69.5 °	70.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	85.0 mm	110.0 mm	128.0 mm	154.0 mm	175.0 mm
C	top tube horizontal	518.0 mm	534.2 mm	554.5 mm	578.4 mm	592.5 mm
D	standover height	759.0 mm	785.0 mm	803.0 mm	824.0 mm	841.0 mm
E	BB offset	76.0 mm	76.0 mm	76.0 mm	76.0 mm	76.0 mm
F	BB height	294.0 mm	294.0 mm	294.0 mm	294.0 mm	294.0 mm
G	wheel base	1,021.5 mm	1,030.1 mm	1,036.8 mm	1,056.2 mm	1,071.1 mm
H	BB center to toptube center					
I	BB center to top of seattube	477.0 mm	507.0 mm	527.0 mm	547.0 mm	567.0 mm
J	seat angle	74.5 °	74.0 °	73.5 °	73.0 °	73.0 °
K	chainstay	435.0 mm	435.0 mm	435.0 mm	435.0 mm	435.0 mm
L	reach	374.0 mm	378.0 mm	387.0 mm	398.0 mm	406.0 mm
M	stack	519.3 mm	544.7 mm	565.6 mm	590.2 mm	610.0 mm
N	stem length	80.0 mm	90.0 mm	100.0 mm	100.0 mm	110.0 mm

0	trail	80.8 mm	77.5 mm	70.7 mm	70.7 mm	70.7 mm
---	-------	---------	---------	---------	---------	---------