



Geometry Chart (INCHES)

| | | S | M | L | XL |
|---|------------------------------|---------|---------|---------|---------|
| A | head tube angle | 65.8 ° | 65.8 ° | 65.8 ° | 65.8 ° |
| B | head tube length | 3.5 in | 3.5 in | 4.1 in | 4.5 in |
| C | top tube horizontal | 22.1 in | 23.2 in | 24.1 in | 25.2 in |
| D | standover height | 29.9 in | 30.2 in | 30.6 in | 31.5 in |
| E | BB offset | -1.7 in | -1.7 in | -1.7 in | -1.7 in |
| F | BB height | 13.1 in | 13.1 in | 13.1 in | 13.1 in |
| G | wheel base | 45.1 in | 46.2 in | 47.4 in | 48.7 in |
| H | BB center to toptube center | | | | |
| I | BB center to top of seattube | 16.3 in | 17.3 in | 19.3 in | 21.3 in |
| J | seat angle | 75.7 ° | 75.9 ° | 76.4 ° | 76.7 ° |
| K | chainstay | 17.2 in | 17.2 in | 17.2 in | 17.2 in |
| L | reach | 16.1 in | 17.3 in | 18.5 in | 19.7 in |
| M | stack | 23.9 in | 23.9 in | 24.3 in | 24.7 in |
| N | stem length | 2.0 in | 2.4 in | 2.4 in | 2.8 in |
| O | trail | 4.2 in | 4.2 in | 4.2 in | 4.2 in |
| P | Fork length | 21.3 in | 21.3 in | 21.3 in | 21.3 in |
| Q | Maximum Seatpost Insertion | 5.9 in | 6.9 in | 8.9 in | 10.8 in |
| R | Crank Length | 6.7 in | 6.9 in | 6.9 in | 6.9 in |

Geometry Chart (MM)

| | | S | M | L | XL |
|---|------------------------------|------------|------------|------------|------------|
| A | head tube angle | 65.8 ° | 65.8 ° | 65.8 ° | 65.8 ° |
| B | head tube length | 90.0 mm | 90.0 mm | 105.0 mm | 115.0 mm |
| C | top tube horizontal | 561.0 mm | 589.0 mm | 613.0 mm | 641.0 mm |
| D | standover height | 759.0 mm | 767.0 mm | 778.0 mm | 801.0 mm |
| E | BB offset | -43.5 mm | -43.5 mm | -43.5 mm | -43.5 mm |
| F | BB height | 331.5 mm | 331.5 mm | 331.5 mm | 331.5 mm |
| G | wheel base | 1,145.0 mm | 1,174.0 mm | 1,205.0 mm | 1,236.0 mm |
| H | BB center to toptube center | | | | |
| I | BB center to top of seattube | 415.0 mm | 440.0 mm | 490.0 mm | 540.0 mm |
| J | seat angle | 75.7 ° | 75.9 ° | 76.4 ° | 76.7 ° |
| K | chainstay | 437.5 mm | 437.5 mm | 437.5 mm | 437.5 mm |

| | | | | | |
|---|----------------------------|----------|----------|----------|----------|
| L | reach | 410.0 mm | 440.0 mm | 470.0 mm | 500.0 mm |
| M | stack | 607.5 mm | 607.5 mm | 617.7 mm | 627.0 mm |
| N | stem length | 50.0 mm | 60.0 mm | 60.0 mm | 70.0 mm |
| O | trail | 107.0 mm | 107.0 mm | 107.0 mm | 107.0 mm |
| P | Fork length | 540.0 mm | 540.0 mm | 540.0 mm | 540.0 mm |
| Q | Maximum Seatpost Insertion | 150.0 mm | 175.0 mm | 225.0 mm | 275.0 mm |
| R | Crank Length | 170.0 mm | 175.0 mm | 175.0 mm | 175.0 mm |