

**Geometry Chart (INCHES)**

|   |                              | <b>S</b> | <b>M</b> | <b>L</b> | <b>XL</b> |
|---|------------------------------|----------|----------|----------|-----------|
| A | head tube angle              | 67.2 °   | 67.2 °   | 67.2 °   | 67.2 °    |
| B | head tube length             | 3.5 in   | 3.5 in   | 4.1 in   | 4.5 in    |
| C | top tube horizontal          | 22.1 in  | 23.2 in  | 24.2 in  | 25.3 in   |
| D | standover height             | 29.8 in  | 30.1 in  | 30.6 in  | 31.5 in   |
| E | BB offset                    | -1.8 in  | -1.8 in  | -1.8 in  | -1.8 in   |
| F | BB height                    | 13.0 in  | 13.0 in  | 13.0 in  | 13.0 in   |
| G | wheel base                   | 44.4 in  | 45.6 in  | 46.9 in  | 48.5 in   |
| H | BB center to toptube center  |          |          |          |           |
| I | BB center to top of seattube | 16.3 in  | 17.3 in  | 19.3 in  | 21.3 in   |
| J | seat angle                   | 75.9 °   | 76.1 °   | 76.6 °   | 76.9 °    |
| K | chainstay                    | 17.2 in  | 17.2 in  | 17.2 in  | 17.2 in   |
| L | reach                        | 16.2 in  | 17.4 in  | 18.5 in  | 19.7 in   |
| M | stack                        | 23.7 in  | 23.7 in  | 24.3 in  | 24.6 in   |
| N | stem length                  | 2.0 in   | 2.4 in   | 2.8 in   | 3.1 in    |
| O | trail                        | 4.5 in   | 4.5 in   | 4.5 in   | 4.5 in    |
| P | Fork length                  | 20.9 in  | 20.9 in  | 20.9 in  | 20.9 in   |
| Q | Maximum Seatpost Insertion   | 5.9 in   | 6.9 in   | 8.9 in   | 10.8 in   |
| R | Crank Length                 | 6.7 in   | 6.9 in   | 6.9 in   | 6.9 in    |

**Geometry Chart (INCHES)**

|   |                              | <b>S</b> | <b>M</b> | <b>L</b> | <b>XL</b> |
|---|------------------------------|----------|----------|----------|-----------|
| A | head tube angle              | 67.2 °   | 67.2 °   | 67.2 °   | 67.2 °    |
| B | head tube length             | 3.5 in   | 3.5 in   | 4.1 in   | 4.5 in    |
| C | top tube horizontal          | 22.1 in  | 23.2 in  | 24.2 in  | 25.3 in   |
| D | standover height             | 29.8 in  | 30.1 in  | 30.6 in  | 31.5 in   |
| E | BB offset                    | -1.8 in  | -1.8 in  | -1.8 in  | -1.8 in   |
| F | BB height                    | 13.0 in  | 13.0 in  | 13.0 in  | 13.0 in   |
| G | wheel base                   | 44.4 in  | 45.6 in  | 46.9 in  | 48.5 in   |
| H | BB center to toptube center  |          |          |          |           |
| I | BB center to top of seattube | 16.3 in  | 17.3 in  | 19.3 in  | 21.3 in   |
| J | seat angle                   | 75.9 °   | 76.1 °   | 76.6 °   | 76.9 °    |
| K | chainstay                    | 17.2 in  | 17.2 in  | 17.2 in  | 17.2 in   |
| L | reach                        | 16.2 in  | 17.4 in  | 18.5 in  | 19.7 in   |
| M | stack                        | 23.7 in  | 23.7 in  | 24.3 in  | 24.6 in   |
| N | stem length                  | 2.0 in   | 2.4 in   | 2.8 in   | 3.1 in    |
| O | trail                        | 4.5 in   | 4.5 in   | 4.5 in   | 4.5 in    |
| P | Fork length                  | 20.9 in  | 20.9 in  | 20.9 in  | 20.9 in   |
| Q | Maximum Seatpost Insertion   | 5.9 in   | 6.9 in   | 8.9 in   | 10.8 in   |
| R | Crank Length                 | 6.7 in   | 6.9 in   | 6.9 in   | 6.9 in    |