



### Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	67.2 °	67.2 °	67.2 °	67.2 °
B	head tube length	3.5 in	3.5 in	4.1 in	4.5 in
C	top tube horizontal	22.1 in	23.2 in	24.2 in	25.3 in
D	standover height	29.8 in	30.1 in	30.6 in	31.5 in
E	BB offset	-1.8 in	-1.8 in	-1.8 in	-1.8 in
F	BB height	13.0 in	13.0 in	13.0 in	13.0 in
G	wheel base	44.4 in	45.6 in	46.9 in	48.5 in
H	BB center to toptube center				
I	BB center to top of seattube	16.3 in	17.3 in	19.3 in	21.3 in
J	seat angle	75.9 °	76.1 °	76.6 °	76.9 °
K	chainstay	17.2 in	17.2 in	17.2 in	17.2 in
L	reach	16.2 in	17.4 in	18.5 in	19.7 in
M	stack	23.7 in	23.7 in	24.3 in	24.6 in
N	stem length	2.0 in	2.4 in	2.8 in	3.1 in
O	trail	4.5 in	4.5 in	4.5 in	4.5 in
P	Fork length	20.9 in	20.9 in	20.9 in	20.9 in
Q	Maximum Seatpost Insertion	5.9 in	6.9 in	8.9 in	10.8 in
R	Crank Length	6.7 in	6.9 in	6.9 in	6.9 in

### Geometry Chart (MM)

		S	M	L	XL
A	head tube angle	67.2 °	67.2 °	67.2 °	67.2 °
B	head tube length	90.0 mm	90.0 mm	105.0 mm	115.0 mm
C	top tube horizontal	562.0 mm	590.0 mm	614.0 mm	642.0 mm
D	standover height	758.0 mm	765.0 mm	776.0 mm	799.0 mm
E	BB offset	-45.0 mm	-45.0 mm	-45.0 mm	-45.0 mm
F	BB height	330.0 mm	330.0 mm	330.0 mm	330.0 mm
G	wheel base	1,129.0 mm	1,159.0 mm	1,190.0 mm	1,231.0 mm
H	BB center to toptube center				
I	BB center to top of seattube	415.0 mm	440.0 mm	490.0 mm	540.0 mm
J	seat angle	75.9 °	76.1 °	76.6 °	76.9 °
K	chainstay	437.5 mm	437.5 mm	437.5 mm	437.5 mm

L	reach	411.0 mm	441.0 mm	471.0 mm	501.0 mm
M	stack	602.5 mm	602.5 mm	616.0 mm	625.0 mm
N	stem length	50.0 mm	60.0 mm	70.0 mm	80.0 mm
O	trail	115.0 mm	115.0 mm	115.0 mm	115.0 mm
P	Fork length	530.0 mm	530.0 mm	530.0 mm	530.0 mm
Q	Maximum Seatpost Insertion	150.0 mm	175.0 mm	225.0 mm	275.0 mm
R	Crank Length	170.0 mm	175.0 mm	175.0 mm	175.0 mm