



Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	64.5 °	65.0 °	65.0 °	65.0 °
B	head tube length	4.7 in	4.9 in	5.3 in	5.7 in
C	top tube horizontal	22.8 in	23.4 in	24.6 in	25.8 in
D	standover height	30.2 in	30.2 in	30.2 in	30.2 in
E	BB offset	-1.2 in	-1.2 in	-1.2 in	-1.2 in
F	BB height	13.7 in	13.7 in	13.7 in	13.7 in
G	wheel base	48.4 in	48.8 in	50.0 in	51.3 in
H	BB center to toptube center				
I	BB center to top of seattube	16.2 in	17.3 in	18.5 in	19.7 in
J	seat angle	77.0 °	76.9 °	76.9 °	76.8 °
K	chainstay	18.2 in	18.2 in	18.2 in	18.2 in
L	reach	17.0 in	17.6 in	18.6 in	19.7 in
M	stack	25.0 in	25.3 in	25.6 in	26.0 in
N	stem length	1.6 in	1.6 in	2.0 in	2.0 in
O	trail	5.2 in	5.1 in	5.1 in	5.1 in
P	Fork length	21.9 in	21.9 in	21.9 in	21.9 in
Q	Maximum Seatpost Insertion	9.6 in	10.4 in	11.8 in	12.6 in
R	Crank Length	6.5 in	6.5 in	6.5 in	6.5 in

Geometry Chart (MM)

		S	M	L	XL
A	head tube angle	64.5 °	65.0 °	65.0 °	65.0 °
B	head tube length	120.0 mm	125.0 mm	135.0 mm	145.0 mm
C	top tube horizontal	579.4 mm	595.0 mm	625.6 mm	656.4 mm
D	standover height	766.0 mm	766.0 mm	766.0 mm	766.0 mm
E	BB offset	-30.0 mm	-30.0 mm	-30.0 mm	-30.0 mm
F	BB height	347.0 mm	347.0 mm	347.0 mm	347.0 mm
G	wheel base	1,228.7 mm	1,238.7 mm	1,270.7 mm	1,302.5 mm
H	BB center to toptube center				
I	BB center to top of seattube	410.5 mm	440.5 mm	470.4 mm	500.4 mm
J	seat angle	77.0 °	76.9 °	76.9 °	76.8 °
K	chainstay	461.0 mm	461.0 mm	461.0 mm	461.0 mm

L	reach	432.7 mm	445.8 mm	473.6 mm	501.2 mm
M	stack	634.8 mm	642.2 mm	651.3 mm	660.4 mm
N	stem length	40.0 mm	40.0 mm	50.0 mm	50.0 mm
O	trail	133.3 mm	129.5 mm	129.5 mm	129.5 mm
P	Fork length	557.1 mm	557.1 mm	557.1 mm	557.1 mm
Q	Maximum Seatpost Insertion	245.0 mm	265.0 mm	300.0 mm	320.0 mm
R	Crank Length	165.0 mm	165.0 mm	165.0 mm	165.0 mm