



Geometry Chart (INCHES)

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting		
A	head tube angle	64.8 °	65.4 °	64.8 °	65.4 °	65.0 °	65.6 °	65.0 °	65.6 °
B	head tube length	4.7 in	4.7 in	4.9 in	4.9 in	5.3 in	5.3 in	5.7 in	5.7 in
C	top tube horizontal	23.0 in	23.0 in	23.8 in	23.8 in	25.0 in	24.9 in	26.2 in	26.1 in
D	standover height	30.0 in	29.5 in	30.2 in	29.7 in	31.4 in	30.9 in	31.9 in	31.4 in
E	BB offset	-1.2 in	-0.9 in	-1.2 in	-0.9 in	-1.2 in	-0.9 in	-1.2 in	-0.9 in
F	BB height	13.7 in	13.3 in	13.7 in	13.3 in	13.7 in	13.3 in	13.7 in	13.3 in
G	wheel base	47.8 in	47.8 in	48.7 in	48.6 in	49.5 in	49.5 in	50.8 in	50.7 in
H	BB center to top tube center								
I	BB center to top of seat tube	16.1 in	16.1 in	17.3 in	17.3 in	19.3 in	19.3 in	21.3 in	21.3 in
J	seat angle	75.4 °	76.0 °	75.4 °	76.0 °	74.8 °	75.4 °	74.8 °	75.4 °
K	chainstay	18.3 in	18.2 in	18.3 in	18.2 in	18.3 in	18.2 in	18.3 in	18.2 in
L	reach	16.6 in	16.9 in	17.3 in	17.6 in	18.1 in	18.4 in	19.2 in	19.5 in
M	stack	24.7 in	24.5 in	24.8 in	24.7 in	25.3 in	25.1 in	25.6 in	25.4 in
N	stem length	2.0 in	2.0 in	2.0 in	2.0 in	2.4 in	2.4 in	2.8 in	2.8 in
O	trail	5.1 in	4.7 in	5.1 in	4.7 in	5.0 in	4.7 in	5.0 in	4.7 in

Geometry Chart (INCHES)

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting		

A	head tube angle	64.8 °	65.4 °	64.8 °	65.4 °	65.0 °	65.6 °	65.0 °	65.6 °
B	head tube length	4.7 in	4.7 in	4.9 in	4.9 in	5.3 in	5.3 in	5.7 in	5.7 in
C	top tube horizontal	23.0 in	23.0 in	23.8 in	23.8 in	25.0 in	24.9 in	26.2 in	26.1 in
D	standover height	30.0 in	29.5 in	30.2 in	29.7 in	31.4 in	30.9 in	31.9 in	31.4 in
E	BB offset	-1.2 in	-0.9 in	-1.2 in	-0.9 in	-1.2 in	-0.9 in	-1.2 in	-0.9 in
F	BB height	13.7 in	13.3 in	13.7 in	13.3 in	13.7 in	13.3 in	13.7 in	13.3 in
G	wheel base	47.8 in	47.8 in	48.7 in	48.6 in	49.5 in	49.5 in	50.8 in	50.7 in
H	BB center to toptube center								
I	BB center to top of seattube	16.1 in	16.1 in	17.3 in	17.3 in	19.3 in	19.3 in	21.3 in	21.3 in
J	seat angle	75.4 °	76.0 °	75.4 °	76.0 °	74.8 °	75.4 °	74.8 °	75.4 °
K	chainstay	18.3 in	18.2 in	18.3 in	18.2 in	18.3 in	18.2 in	18.3 in	18.2 in
L	reach	16.6 in	16.9 in	17.3 in	17.6 in	18.1 in	18.4 in	19.2 in	19.5 in
M	stack	24.7 in	24.5 in	24.8 in	24.7 in	25.3 in	25.1 in	25.6 in	25.4 in
N	stem length	2.0 in	2.0 in	2.0 in	2.0 in	2.4 in	2.4 in	2.8 in	2.8 in
O	trail	5.1 in	4.7 in	5.1 in	4.7 in	5.0 in	4.7 in	5.0 in	4.7 in