



### Geometry Chart (INCHES)

|   |                              | S       | M       | L       | XL      |
|---|------------------------------|---------|---------|---------|---------|
| A | head tube angle              | 69.5 °  | 70.0 °  | 70.5 °  | 70.5 °  |
| B | head tube length             | 5.1 in  | 5.5 in  | 6.3 in  | 7.3 in  |
| C | top tube horizontal          | 22.8 in | 23.6 in | 24.4 in | 25.2 in |
| D | standover height             | 30.5 in | 31.7 in | 32.7 in | 34.2 in |
| E | BB offset                    | 3.0 in  | 3.0 in  | 3.0 in  | 3.0 in  |
| F | BB height                    | 17.3 in | 17.3 in | 17.3 in | 17.3 in |
| G | wheel base                   | 45.0 in | 45.2 in | 45.9 in | 46.7 in |
| H | BB center to toptube center  |         |         |         |         |
| I | BB center to top of seattube | 17.3 in | 18.9 in | 20.5 in | 22.0 in |
| J | seat angle                   | 74.5 °  | 74.5 °  | 74.5 °  | 74.5 °  |
| K | chainstay                    | 18.9 in | 18.9 in | 18.9 in | 18.9 in |
| L | reach                        | 15.9 in | 16.6 in | 17.2 in | 17.7 in |
| M | stack                        | 24.8 in | 25.2 in | 26.1 in | 27.0 in |
| N | stem length                  | 4.3 in  | 4.3 in  | 4.3 in  | 4.3 in  |
| O | trail                        | 3.5 in  | 3.4 in  | 3.2 in  | 3.2 in  |

### Geometry Chart (MM)

|   |                              | S          | M          | L          | XL         |
|---|------------------------------|------------|------------|------------|------------|
| A | head tube angle              | 69.5 °     | 70.0 °     | 70.5 °     | 70.5 °     |
| B | head tube length             | 130.0 mm   | 140.0 mm   | 160.0 mm   | 185.0 mm   |
| C | top tube horizontal          | 580.0 mm   | 600.0 mm   | 620.0 mm   | 640.0 mm   |
| D | standover height             | 775.0 mm   | 804.0 mm   | 831.0 mm   | 869.0 mm   |
| E | BB offset                    | 75.0 mm    | 75.0 mm    | 75.0 mm    | 75.0 mm    |
| F | BB height                    | 440.5 mm   | 440.5 mm   | 440.5 mm   | 440.5 mm   |
| G | wheel base                   | 1,142.0 mm | 1,149.0 mm | 1,165.0 mm | 1,187.0 mm |
| H | BB center to toptube center  |            |            |            |            |
| I | BB center to top of seattube | 440.0 mm   | 480.0 mm   | 520.0 mm   | 560.0 mm   |
| J | seat angle                   | 74.5 °     | 74.5 °     | 74.5 °     | 74.5 °     |
| K | chainstay                    | 480.0 mm   | 480.0 mm   | 480.0 mm   | 480.0 mm   |
| L | reach                        | 405.0 mm   | 422.0 mm   | 436.0 mm   | 450.0 mm   |
| M | stack                        | 630.0 mm   | 641.0 mm   | 662.0 mm   | 685.0 mm   |
| N | stem length                  | 110.0 mm   | 110.0 mm   | 110.0 mm   | 110.0 mm   |

|   |       |         |         |         |         |
|---|-------|---------|---------|---------|---------|
| 0 | trail | 89.5 mm | 86.0 mm | 82.5 mm | 82.5 mm |
|---|-------|---------|---------|---------|---------|