



Geometry Chart (INCHES)

| | | XS | S / 700 | M / 900 | L / 900 |
|---|------------------------------|-----------|----------------|----------------|----------------|
| A | head tube angle | 69.5 ° | 69.5 ° | 69.5 ° | 69.5 ° |
| B | head tube length | 6.7 in | 6.7 in | 6.7 in | 6.7 in |
| C | top tube horizontal | 23.4 in | 23.6 in | 23.8 in | 24.0 in |
| D | standover height | 19.7 in | 19.7 in | 19.7 in | 19.7 in |
| E | BB offset | -2.8 in | -2.8 in | -2.8 in | -2.8 in |
| F | BB height | 12.0 in | 12.0 in | 12.0 in | 12.0 in |
| G | wheel base | 45.3 in | 45.5 in | 45.7 in | 45.9 in |
| H | BB center to toptube center | | | | |
| I | BB center to top of seattube | 17.3 in | 18.9 in | 20.5 in | 22.0 in |
| J | seat angle | 72.5 ° | 72.5 ° | 72.5 ° | 72.5 ° |
| K | chainstay | 19.9 in | 19.9 in | 19.9 in | 19.9 in |
| L | reach | 15.4 in | 15.6 in | 15.8 in | 16.0 in |
| M | stack | 25.3 in | 25.3 in | 25.3 in | 25.3 in |
| N | stem length | | | | |
| O | trail | | | | |

Geometry Chart (INCHES)

| | | XS | S / 700 | M / 900 | L / 900 |
|---|------------------------------|-----------|----------------|----------------|----------------|
| A | head tube angle | 69.5 ° | 69.5 ° | 69.5 ° | 69.5 ° |
| B | head tube length | 6.7 in | 6.7 in | 6.7 in | 6.7 in |
| C | top tube horizontal | 23.4 in | 23.6 in | 23.8 in | 24.0 in |
| D | standover height | 19.7 in | 19.7 in | 19.7 in | 19.7 in |
| E | BB offset | -2.8 in | -2.8 in | -2.8 in | -2.8 in |
| F | BB height | 12.0 in | 12.0 in | 12.0 in | 12.0 in |
| G | wheel base | 45.3 in | 45.5 in | 45.7 in | 45.9 in |
| H | BB center to toptube center | | | | |
| I | BB center to top of seattube | 17.3 in | 18.9 in | 20.5 in | 22.0 in |
| J | seat angle | 72.5 ° | 72.5 ° | 72.5 ° | 72.5 ° |
| K | chainstay | 19.9 in | 19.9 in | 19.9 in | 19.9 in |
| L | reach | 15.4 in | 15.6 in | 15.8 in | 16.0 in |
| M | stack | 25.3 in | 25.3 in | 25.3 in | 25.3 in |
| N | stem length | | | | |

