



### Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	70.0 °	70.0 °	70.0 °	70.0 °
B	head tube length	4.5 in	5.1 in	6.1 in	7.1 in
C	top tube horizontal	21.7 in	22.2 in	22.6 in	23.2 in
D	standover height	26.8 in	26.9 in	27.4 in	27.7 in
E	BB offset	2.2 in	2.2 in	2.2 in	2.2 in
F	BB height	16.0 in	16.0 in	16.0 in	16.0 in
G	wheel base	42.0 in	42.4 in	42.6 in	43.3 in
H	BB center to toptube center				
I	BB center to top of seattube	16.5 in	18.1 in	19.7 in	21.3 in
J	seat angle	73.5 °	73.0 °	72.3 °	72.0 °
K	chainstay	18.0 in	18.0 in	18.0 in	18.0 in
L	reach	14.7 in	14.9 in	14.8 in	15.1 in
M	stack				
N	stem length	2.8 in	3.1 in	3.5 in	3.9 in
O	trail				

### Geometry Chart (MM)

		S	M	L	XL
A	head tube angle	70.0 °	70.0 °	70.0 °	70.0 °
B	head tube length	115.0 mm	130.0 mm	155.0 mm	180.0 mm
C	top tube horizontal	550.0 mm	565.0 mm	575.0 mm	590.0 mm
D	standover height	679.5 mm	684.1 mm	695.8 mm	702.6 mm
E	BB offset	56.0 mm	56.0 mm	56.0 mm	56.0 mm
F	BB height	406.0 mm	406.0 mm	406.0 mm	406.0 mm
G	wheel base	1,067.0 mm	1,078.0 mm	1,083.0 mm	1,099.0 mm
H	BB center to toptube center				
I	BB center to top of seattube	420.0 mm	460.0 mm	500.0 mm	540.0 mm
J	seat angle	73.5 °	73.0 °	72.3 °	72.0 °
K	chainstay	456.0 mm	456.0 mm	456.0 mm	456.0 mm
L	reach	374.0 mm	379.0 mm	375.9 mm	383.5 mm
M	stack				
N	stem length	70.0 mm	80.0 mm	90.0 mm	100.0 mm

