



Geometry Chart (INCHES)

		S	M	L
A	head tube angle	69.5 °	70.0 °	70.5 °
B	head tube length	5.1 in	5.5 in	6.3 in
C	top tube horizontal	22.8 in	23.5 in	24.3 in
D	standover height	27.0 in	26.9 in	27.0 in
E	BB offset	-2.9 in	-2.9 in	-2.9 in
F	BB height	11.5 in	11.5 in	11.5 in
G	wheel base	45.0 in	45.6 in	46.2 in
H	BB center to toptube center			
I	BB center to top of seattube	17.3 in	18.9 in	20.5 in
J	seat angle	74.5 °	74.5 °	74.5 °
K	chainstay	19.3 in	19.3 in	19.3 in
L	reach	15.9 in	16.6 in	17.1 in
M	stack	24.8 in	25.2 in	26.1 in
N	stem length	4.3 in	4.3 in	4.3 in
O	trail	3.5 in	3.4 in	3.2 in

Geometry Chart (MM)

		S	M	L
A	head tube angle	69.5 °	70.0 °	70.5 °
B	head tube length	130.0 mm	140.0 mm	160.0 mm
C	top tube horizontal	579.0 mm	598.0 mm	618.0 mm
D	standover height	686.0 mm	684.0 mm	687.0 mm
E	BB offset	-74.0 mm	-74.0 mm	-74.0 mm
F	BB height	291.0 mm	291.0 mm	291.0 mm
G	wheel base	1,143.0 mm	1,158.0 mm	1,174.0 mm
H	BB center to toptube center			
I	BB center to top of seattube	440.0 mm	480.0 mm	520.0 mm
J	seat angle	74.5 °	74.5 °	74.5 °
K	chainstay	490.0 mm	490.0 mm	490.0 mm
L	reach	404.0 mm	421.0 mm	435.0 mm
M	stack	629.0 mm	640.0 mm	662.0 mm
N	stem length	110.0 mm	110.0 mm	110.0 mm

0	trail	89.5 mm	86.0 mm	82.5 mm
---	-------	---------	---------	---------