

## **Geometry Chart (INCHES)**

		S	M	L	XL
A	head tube angle	69.5 °	70.0 °	70.5 °	70.5 °
В	head tube length	5.1 in	5.5 in	6.3 in	7.3 in
C	top tube horizontal	22.8 in	23.6 in	24.4 in	25.2 in
D	standover height	30.5 in	31.7 in	32.7 in	34.2 in
E	BB offset	3.0 in	3.0 in	3.0 in	3.0 in
F	BB height	17.3 in	17.3 in	17.3 in	17.3 in
G	wheel base	45.0 in	45.2 in	45.9 in	46.7 in
H	BB center to toptube center				
I	BB center to top of seattube	17.3 in	18.9 in	20.5 in	22.0 in
J	seat angle	74.5 °	74.5 °	74.5 °	74.5 °
K	chainstay	18.9 in	18.9 in	18.9 in	18.9 in
L	reach	15.9 in	16.6 in	17.2 in	17.7 in
M	stack	24.8 in	25.2 in	26.1 in	27.0 in
N	stem length	4.3 in	4.3 in	4.3 in	4.3 in
0	trail	3.5 in	3.4 in	3.2 in	3.2 in

## **Geometry Chart (INCHES)**

		S	M	L	XL
A	head tube angle	69.5 °	70.0 °	70.5 °	70.5 °
В	head tube length	5.1 in	5.5 in	6.3 in	7.3 in
C	top tube horizontal	22.8 in	23.6 in	24.4 in	25.2 in
D	standover height	30.5 in	31.7 in	32.7 in	34.2 in
E	BB offset	3.0 in	3.0 in	3.0 in	3.0 in
F	BB height	17.3 in	17.3 in	17.3 in	17.3 in
G	wheel base	45.0 in	45.2 in	45.9 in	46.7 in
Η	BB center to toptube center				
I	BB center to top of seattube	17.3 in	18.9 in	20.5 in	22.0 in
J	seat angle	74.5 °	74.5 °	74.5 °	74.5 °
K	chainstay	18.9 in	18.9 in	18.9 in	18.9 in
L	reach	15.9 in	16.6 in	17.2 in	17.7 in
M	stack	24.8 in	25.2 in	26.1 in	27.0 in
N	stem length	4.3 in	4.3 in	4.3 in	4.3 in