



**Geometry Chart (INCHES)**

|   |                              | <b>XS</b> | <b>S / 700</b> | <b>M / 900</b> | <b>L / 900</b> |
|---|------------------------------|-----------|----------------|----------------|----------------|
| A | head tube angle              | 69.5 °    | 69.5 °         | 69.5 °         | 69.5 °         |
| B | head tube length             | 6.7 in    | 6.7 in         | 6.7 in         | 6.7 in         |
| C | top tube horizontal          | 23.4 in   | 23.6 in        | 23.8 in        | 24.0 in        |
| D | standover height             | 19.7 in   | 19.7 in        | 19.7 in        | 19.7 in        |
| E | BB offset                    | -2.8 in   | -2.8 in        | -2.8 in        | -2.8 in        |
| F | BB height                    | 12.0 in   | 12.0 in        | 12.0 in        | 12.0 in        |
| G | wheel base                   | 45.3 in   | 45.5 in        | 45.7 in        | 45.9 in        |
| H | BB center to toptube center  |           |                |                |                |
| I | BB center to top of seattube | 17.3 in   | 18.9 in        | 20.5 in        | 22.0 in        |
| J | seat angle                   | 72.5 °    | 72.5 °         | 72.5 °         | 72.5 °         |
| K | chainstay                    | 19.9 in   | 19.9 in        | 19.9 in        | 19.9 in        |
| L | reach                        | 15.4 in   | 15.6 in        | 15.8 in        | 16.0 in        |
| M | stack                        | 25.3 in   | 25.3 in        | 25.3 in        | 25.3 in        |
| N | stem length                  |           |                |                |                |
| O | trail                        |           |                |                |                |

**Geometry Chart (MM)**

|   |                              | <b>XS</b>  | <b>S / 700</b> | <b>M / 900</b> | <b>L / 900</b> |
|---|------------------------------|------------|----------------|----------------|----------------|
| A | head tube angle              | 69.5 °     | 69.5 °         | 69.5 °         | 69.5 °         |
| B | head tube length             | 170.0 mm   | 170.0 mm       | 170.0 mm       | 170.0 mm       |
| C | top tube horizontal          | 595.0 mm   | 600.0 mm       | 605.0 mm       | 610.0 mm       |
| D | standover height             | 499.3 mm   | 499.3 mm       | 499.3 mm       | 499.3 mm       |
| E | BB offset                    | -70.0 mm   | -70.0 mm       | -70.0 mm       | -70.0 mm       |
| F | BB height                    | 304.0 mm   | 304.0 mm       | 304.0 mm       | 304.0 mm       |
| G | wheel base                   | 1,151.2 mm | 1,156.2 mm     | 1,161.2 mm     | 1,166.2 mm     |
| H | BB center to toptube center  |            |                |                |                |
| I | BB center to top of seattube | 440.0 mm   | 480.0 mm       | 520.0 mm       | 560.0 mm       |
| J | seat angle                   | 72.5 °     | 72.5 °         | 72.5 °         | 72.5 °         |
| K | chainstay                    | 505.0 mm   | 505.0 mm       | 505.0 mm       | 505.0 mm       |
| L | reach                        | 392.1 mm   | 397.1 mm       | 402.1 mm       | 407.1 mm       |
| M | stack                        | 643.6 mm   | 643.6 mm       | 643.6 mm       | 643.6 mm       |
| N | stem length                  |            |                |                |                |

