



Geometry Chart (INCHES)

		XS	S / 700	M / 900	L / 900
A	head tube angle	69.5 °	69.5 °	69.5 °	69.5 °
B	head tube length	6.7 in	6.7 in	6.7 in	6.7 in
C	top tube horizontal	23.4 in	23.6 in	23.8 in	24.0 in
D	standover height	19.7 in	19.7 in	19.7 in	19.7 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	12.0 in	12.0 in	12.0 in	12.0 in
G	wheel base	45.3 in	45.5 in	45.7 in	45.9 in
H	BB center to toptube center				
I	BB center to top of seattube	17.3 in	18.9 in	20.5 in	22.0 in
J	seat angle	72.5 °	72.5 °	72.5 °	72.5 °
K	chainstay	19.9 in	19.9 in	19.9 in	19.9 in
L	reach	15.4 in	15.6 in	15.8 in	16.0 in
M	stack	25.3 in	25.3 in	25.3 in	25.3 in
N	stem length				
O	trail				

Geometry Chart (INCHES)

		XS	S / 700	M / 900	L / 900
A	head tube angle	69.5 °	69.5 °	69.5 °	69.5 °
B	head tube length	6.7 in	6.7 in	6.7 in	6.7 in
C	top tube horizontal	23.4 in	23.6 in	23.8 in	24.0 in
D	standover height	19.7 in	19.7 in	19.7 in	19.7 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	12.0 in	12.0 in	12.0 in	12.0 in
G	wheel base	45.3 in	45.5 in	45.7 in	45.9 in
H	BB center to toptube center				
I	BB center to top of seattube	17.3 in	18.9 in	20.5 in	22.0 in
J	seat angle	72.5 °	72.5 °	72.5 °	72.5 °
K	chainstay	19.9 in	19.9 in	19.9 in	19.9 in
L	reach	15.4 in	15.6 in	15.8 in	16.0 in
M	stack	25.3 in	25.3 in	25.3 in	25.3 in
N	stem length				

