



Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	69.5 °	70.0 °	70.5 °	70.5 °
B	head tube length	5.1 in	5.5 in	6.3 in	7.3 in
C	top tube horizontal	22.8 in	23.6 in	24.4 in	25.2 in
D	standover height	30.5 in	31.7 in	32.7 in	34.2 in
E	BB offset	3.0 in	3.0 in	3.0 in	3.0 in
F	BB height	17.3 in	17.3 in	17.3 in	17.3 in
G	wheel base	45.0 in	45.2 in	45.9 in	46.7 in
H	BB center to toptube center				
I	BB center to top of seattube	17.3 in	18.9 in	20.5 in	22.0 in
J	seat angle	74.5 °	74.5 °	74.5 °	74.5 °
K	chainstay	18.9 in	18.9 in	18.9 in	18.9 in
L	reach	15.9 in	16.6 in	17.2 in	17.7 in
M	stack	24.8 in	25.2 in	26.1 in	27.0 in
N	stem length	4.3 in	4.3 in	4.3 in	4.3 in
O	trail	3.5 in	3.4 in	3.2 in	3.2 in

Geometry Chart (MM)

		S	M	L	XL
A	HEAD TUBE ANGLE	69.5 °	70.0 °	70.5 °	70.5 °
B	HEAD TUBE LENGTH	130.0 MM	140.0 MM	160.0 MM	185.0 MM
C	TOP TUBE HORIZONTAL	580.0 MM	600.0 MM	620.0 MM	640.0 MM
D	STANDOVER HEIGHT	775.0 MM	804.0 MM	831.0 MM	869.0 MM
E	BB OFFSET	75.0 MM	75.0 MM	75.0 MM	75.0 MM
F	BB HEIGHT	440.5 MM	440.5 MM	440.5 MM	440.5 MM
G	WHEEL BASE	1,142.0 MM	1,149.0 MM	1,165.0 MM	1,187.0 MM
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	440.0 MM	480.0 MM	520.0 MM	560.0 MM
J	SEAT ANGLE	74.5 °	74.5 °	74.5 °	74.5 °
K	CHAINSTAY	480.0 MM	480.0 MM	480.0 MM	480.0 MM
L	REACH	405.0 MM	422.0 MM	436.0 MM	450.0 MM
M	STACK	630.0 MM	641.0 MM	662.0 MM	685.0 MM
N	STEM LENGTH	110.0 MM	110.0 MM	110.0 MM	110.0 MM

