

Bike Geometry & Size Chart - 2025 Intense Tracer 279 PRO

SM (HIGH)	MD (HIGH)	LG (HIGH)	XL (HIGH)	GEOMETRY	SM (LOW)	MD (LOW)	LG (LOW)	XL (LOW)
425mm	455mm	480mm	505mm	REACH	420mm	450mm	475mm	500mm
64.5°	64.5°	64.5°	64.5°	HEADTUBE ANGLE	64°	64°	64°	64°
78°	78°	78°	78°	SEATTUBE ANGLE (Effective)	77.5°	77.5°	77.5°	77.5°
73°	73°	73°	73°	SEATUBE ANGLE (Actual)	72.5°	72.5°	72.5°	72.5°
1193mm	1228mm	1257mm	1286mm	WHEELBASE	1195mm	1229mm	1258mm	1288mm
437mm	437mm	437mm	437mm	CHAINSTAY LENGTH	438mm	438mm	438mm	438mm
756mm	791mm	820mm	849mm	FRONT CENTER	756mm	791mm	820mm	849mm
349mm	349mm	349mm	349mm	BB HEIGHT	342mm	342mm	342mm	342mm
618mm	627mm	636mm	645mm	STACK	618mm	631mm	640mm	650mm
557mm	589mm	617mm	645mm	TOPTUBE LENGTH	557mm	591mm	619mm	647mm
90mm	100mm	110mm	120mm	HEADTUBE LENGTH	90mm	100mm	110mm	120mm
25mm	25mm	25mm	25mm	BB DROP FRONT WHEEL	32mm	32mm	32mm	32mm
5mm	5mm	5mm	5mm	BB DROP REAR WHEEL	12mm	12mm	12mm	12mm
385mm	418mm	440mm	465mm	SEATTUBE LENGTH	385mm	418mm	440mm	465mm
200mm	260mm	260mm	280mm	MAX SEATPOST DEPTH	200mm	260mm	260mm	280mm



NOTE: SIZING IS A PERSONAL PREFERENCE AND THIS IS MEANT AS A GENERAL GUIDE