



### Geometry Chart (INCHES)

		<b>XXS/47</b>	<b>XS/49</b>	<b>S/52</b>	<b>M/54</b>	<b>L/56</b>	<b>XL/58</b>	<b>XXL/61</b>
A	head tube angle	70.5 °	71.0 °	72.0 °	72.5 °	73.0 °	73.3 °	73.3 °
B	head tube length	3.8 in	4.0 in	4.5 in	5.3 in	6.1 in	6.9 in	7.6 in
C	top tube horizontal	20.5 in	20.9 in	21.3 in	21.7 in	22.2 in	22.8 in	23.6 in
D	standover height	28.3 in	29.1 in	29.7 in	30.6 in	31.4 in	32.2 in	33.0 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	10.8 in	10.8 in	10.8 in	10.8 in	10.8 in	10.8 in	10.8 in
G	Addict RC	38.9 in	39.1 in	39.0 in	39.1 in	39.4 in	39.7 in	40.3 in
H	BB center to toptube center	16.1 in	16.9 in	18.1 in	18.9 in	19.7 in	20.5 in	21.7 in
I	BB center to top of seattube	18.5 in	19.3 in	20.5 in	21.3 in	22.0 in	22.8 in	24.0 in
J	seat angle	74.5 °	74.5 °	74.0 °	73.6 °	73.3 °	73.0 °	72.5 °
K	chainstay	16.1 in	16.1 in	16.1 in	16.1 in	16.1 in	16.1 in	16.1 in
L	reach	15.0 in	15.3 in	15.3 in	15.4 in	15.6 in	15.7 in	16.1 in
M	stack	19.8 in	20.1 in	20.7 in	21.6 in	22.4 in	23.1 in	23.9 in
N	stem length	3.5 in	3.5 in	3.9 in	4.3 in	4.3 in	4.7 in	4.7 in
O	centre saddle - centre bar (hor.)	25.0 in	25.6 in	26.5 in	27.3 in	28.0 in	29.0 in	30.0 in
P	centre saddle - centre bar (vert.)	3.6 in	4.1 in	4.2 in	4.1 in	3.9 in	4.2 in	4.5 in
Q	reach centre bar	17.9 in	18.2 in	18.7 in	19.1 in	19.4 in	20.0 in	20.4 in
R	stack centre bar	22.2 in	22.4 in	23.1 in	23.9 in	24.7 in	25.6 in	26.3 in

### Geometry Chart (MM)

		<b>XXS/47</b>	<b>XS/49</b>	<b>S/52</b>	<b>M/54</b>	<b>L/56</b>	<b>XL/58</b>	<b>XXL/61</b>
A	head tube angle	70.5 °	71.0 °	72.0 °	72.5 °	73.0 °	73.3 °	73.3 °
B	head tube length	97.0 mm	102.0 mm	115.0 mm	135.0 mm	155.0 mm	175.0 mm	193.0 mm
C	top tube horizontal	520.0 mm	530.0 mm	540.0 mm	550.0 mm	565.0 mm	580.0 mm	600.0 mm
D	standover height	720.0 mm	740.0 mm	755.0 mm	778.0 mm	798.0 mm	818.0 mm	838.0 mm
E	BB offset	-70.0 mm	-70.0 mm	-70.0 mm	-70.0 mm	-70.0 mm	-70.0 mm	-70.0 mm
F	BB height	274.5 mm	274.5 mm	274.5 mm	274.5 mm	274.5 mm	274.5 mm	274.5 mm
G	Addict RC	987.5 mm	994.0 mm	991.0 mm	992.0 mm	1,000.0 mm	1,008.0 mm	1,023.0 mm
H	BB center to toptube center	410.0 mm	430.0 mm	460.0 mm	480.0 mm	500.0 mm	520.0 mm	550.0 mm
I	BB center to top of seattube	470.0 mm	490.0 mm	520.0 mm	540.0 mm	560.0 mm	580.0 mm	610.0 mm
J	seat angle	74.5 °	74.5 °	74.0 °	73.6 °	73.3 °	73.0 °	72.5 °
K	chainstay	410.0 mm	410.0 mm	410.0 mm	410.0 mm	410.0 mm	410.0 mm	410.0 mm
L	reach	380.0 mm	388.0 mm	389.0 mm	390.0 mm	395.0 mm	400.0 mm	410.0 mm

M	stack	504.0 mm	511.0 mm	526.5 mm	548.0 mm	568.5 mm	588.0 mm	606.0 mm
N	stem length	90.0 mm	90.0 mm	100.0 mm	110.0 mm	110.0 mm	120.0 mm	120.0 mm
O	centre saddle - centre bar (hor.)	635.0 mm	650.0 mm	674.0 mm	694.0 mm	710.0 mm	736.0 mm	761.0 mm
P	centre saddle - centre bar (vert.)	92.0 mm	105.0 mm	106.0 mm	103.0 mm	100.0 mm	106.0 mm	115.0 mm
Q	reach centre bar	454.0 mm	463.0 mm	474.0 mm	485.0 mm	492.0 mm	507.0 mm	518.0 mm
R	stack centre bar	563.0 mm	570.0 mm	586.0 mm	607.0 mm	627.5 mm	649.0 mm	667.0 mm