


2025 Scott Metrix 30 EQ Bike



Geometry Chart (Inches)

Sl no.	Specifications	XXS/47	XS/49	S/52	M/54	L/56	XL/58	XXL/61
A	head tube angle	70.0 °	70.0 °	70.0 °	71.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	3.7 in	4.1 in	4.8 in	5.6 in	6.4 in	7.2 in	8.0 in
C	top tube horizontal	20.2 in	20.6 in	21.1 in	21.9 in	22.5 in	22.9 in	23.4 in
D	standover height	29.4 in	30.0 in	30.9 in	31.7 in	32.5 in	33.2 in	34.2 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.1 in	11.1 in	11.1 in	11.1 in	11.1 in	11.1 in	11.1 in
G	wheel base	40.1 in	40.4 in	40.9 in	41.1 in	41.6 in	42.0 in	42.2 in
H	BB center to toptube center	16.9 in	17.7 in	18.9 in	19.7 in	20.5 in	21.3 in	22.4 in

I	BB center to top of seattube	18.5 in	19.3 in	20.5 in	21.3 in	22.0 in	22.8 in	24.0 in
J	seat angle	75.0 °	74.5 °	74.0 °	73.0 °	72.5 °	72.5 °	72.5 °
K	chainstay	17.1 in	17.1 in	17.1 in	17.3 in	17.3 in	17.3 in	17.3 in
L	reach	14.7 in	14.9 in	15.0 in	15.2 in	15.4 in	15.6 in	15.9 in
M	stack	20.4 in	20.8 in	21.5 in	22.4 in	23.2 in	23.9 in	24.7 in
N	stem length	2.9 in	3.3 in	3.7 in	4.1 in	4.1 in	4.4 in	4.4 in

Geometry Chart (MM)

SI no.	Specifications	XXS/47	XS/49	S/52	M/54	L/56	XL/58	XXL/61
A	head tube angle	70.0 °	70.0 °	70.0 °	71.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	93.0 mm	103.0 mm	123.0 mm	143.0 mm	163.0 mm	183.0 mm	203.0 mm
C	top tube horizontal	512.3 mm	523.0 mm	536.5 mm	556.5 mm	571.2 mm	581.2 mm	594.2 mm
D	standover height	747.0 mm	762.0 mm	786.0 mm	806.0 mm	825.0 mm	844.0 mm	869.0 mm
E	BB offset	-71.0 mm	-71.0 mm	-71.0 mm	-71.0 mm	-71.0 mm	-71.0 mm	-71.0 mm
F	BB height	283.0 mm	283.0 mm	283.0 mm	283.0 mm	283.0 mm	283.0 mm	283.0 mm
G	wheel base	1,019.5 mm	1,026.9 mm	1,037.7 mm	1,044.9 mm	1,056.4 mm	1,067.0 mm	1,071.3 mm
H	BB center to toptube center	430.0 mm	450.0 mm	480.0 mm	500.0 mm	520.0 mm	540.0 mm	570.0 mm
I	BB center to top of seattube	470.0 mm	490.0 mm	520.0 mm	540.0 mm	560.0 mm	580.0 mm	610.0 mm
J	seat angle	75.0 °	74.5 °	74.0 °	73.0 °	72.5 °	72.5 °	72.5 °
K	chainstay	435.0 mm	435.0 mm	435.0 mm	439.0 mm	439.0 mm	439.0 mm	439.0 mm
L	reach	374.0 mm	378.0 mm	382.0 mm	387.0 mm	392.0 mm	396.0 mm	403.0 mm
M	stack	519.0 mm	528.4 mm	547.2 mm	570.0 mm	588.9 mm	607.8 mm	626.8 mm
N	stem length	73.0 mm	83.0 mm	93.0 mm	103.0 mm	103.0 mm	113.0 mm	113.0 mm