

2026 Cervelo ZFS-5 XTR - Specofications

	XTR
Sizes	SM, MD, LG, XL
Fork	Fox 32 Step-cast Factory, 100mm travel
Headset	FSA IS2 1-1/2 x 1-1/2
Stem	Race Face Aeffect Alloy, 35mm clamp, 6 degree
Handlebar	Race Face Next Carbon, 35mm clamp, 760mm width, 10mm rise
Seatpost	Cervélo SP29 Carbon 30.9
Saddle	Prologo Dimension NDR Nack
Shifters	Shimano XTR, M9100, 12 speed
Brake Calipers	Shimano XTR 2 piston
Brake Levers	Shimano XTR M9100 2 Piston
Brake Rotor	Shimano MT900 Centerlock
Rear Derailleur	Shimano XTR, M9100 SGS, 12 speed
Cassette	Shimano M9101, 10-51, 12 speed
Chain	Shimano M9100, 12 speed
Crankset	Shimano XTR, M9125, 32T, 12 Speed
Bottom Bracket	Shimano XTR, BSA, 73mm
Wheels	Reserve 28 XC, 28mm IW, DT Swiss 240,12x148mm, MS freehub, 24H, centerlock, tubeless compatible, Reserve 28 XC, 28mm IW, DT Swiss 240, 15x110mm, 24H, centerlock, tubeless compatible
Thru Axles	Cervelo Thru-axle, 12x148
Tires	Maxxis Rekon Race, EXO 120TPI, 29x2.4
Max Tire Width (Actual)	60mm (2.4")
Shock	Fox Factory Float SL, 2 position remote damper, 190mm x 40mm