

2026 Cervelo ZFS-5 XX SL AXS - Specifications

	XX SL AXS
Sizes	SM, MD, LG, XL
Fork	Rockshox SID SL Ultimate, DebonAir spring, 2 position remote Charger Race Day damper, tapered steerer, 15x110mm, Maxle Stealth, 44mm offset, 100mm travel
Headset	FSA IS2 1-1/2 x 1-1/2
Stem	Race Face Aeffect Alloy, 35mm clamp, 6 degree
Handlebar	Race Face Next Carbon, 35mm clamp, 760mm width, 10mm rise
Seatpost	Cervelo SP29 Carbon 30.9
Saddle	Prologo Dimension NDR Nack
Shifters	SRAM Pod AXS controller
Brake Calipers	SRAM Level Ultimate 4 Piston
Brake Levers	SRAM Level Ultimate Stealth 4 piston
Brake Rotor	SRAM CLX Centerlock
Rear Derailleur	SRAM XX SL Eagle AXS, 12 speed
Cassette	SRAM XX SL, 10-52, 12 Speed
Chain	SRAM XX SL, 12 speed
Crankset	SRAM XX SL Eagle, 32T, Boost 148 DUB
Bottom Bracket	SRAM DUB, BSA 73mm
Wheels	Rear: Reserve 28 XC, 28mm IW, DT Swiss 240, 12x148mm, XD freehub, 24H, centerlock, tubeless compatible Front: Reserve 28 XC, 28mm IW, DT Swiss 240, 15x110mm, 24H, centerlock, tubeless compatible
Thru Axles	Cervelo Thru-axle, 12x148
Tires	Maxxis Rekon Race, EXO 120TPI, 29x2.4
Max Tire Width (Actual)	60mm (2.4")
Shock	Rockshox SIDLuxe Ultimate, RL 2 position remote damper, 190 x 40mm