

2026 Cervelo ZHT-5 GX AXS - Specifications

	GX AXS
Sizes	SM, MD, LG, XL
Fork	Rockshox SID SL Select, DebonAir spring, Charger RL damper, tapered steerer, 15x110mm, Maxle Stealth, 44mm offset, 100mm travel
Handlebar	Race Face Aeffect Alloy, 35mm clamp, 760mm width, 10mm rise
Stem	Race Face Aeffect Alloy, 35mm clamp, 6 degree
Seatpost	Race Face Ride XC Alloy 30.9
Saddle	Prologo Dimension NDR T4.0
Bottom Bracket	SRAM DUB, BSA 73mm
Headset	FSA IS2 1-1/2 x 1-1/2
Tires	Maxxis Rekon Race, EXO 120TPI, 29x2.4
Crankset	SRAM GX Eagle, 32T, Boost 148 DUB
Chain	SRAM GX Eagle, 12 speed
Cassette	SRAM GX Eagle, 10-52, 12 Speed
Rear Derailleur	SRAM GX Eagle AXS, 12 speed
Max Tire Width (Actual)	60mm (2.4")
Shifters	SRAM GX AXS Rocker
Brake Calipers	SRAM Level TL
Brake Levers	SRAM Level TL
Wheels	Rear: Race Face ARC Offset 27, 27mm IW, E*thirteen TRS Race, 12x148mm, XD freehub, 28H, 6 bolt, tubeless compatible Front: Race Face ARC Offset 27, 27mm IW, E*thirteen TRS Race TC, 15x110mm, 24H, 6 bolt, tubeless compatible
Thru Axles	Cervelo Thru-axle, 12x148
Brake Rotor	