

2026 Cervelo ZHT-5 XX1 AXS - Specifications

	XX1 AXS
Sizes	SM, MD, LG, XL
Fork	Rockshox SID SL Ultimate, DebonAir spring, 2 position remote Charger Race Day damper, tapered steerer, 15x110mm, Maxle Stealth, 44mm offset, 100mm travel
Handlebar	Race Face Next SL Carbon, 35mm clamp, 740mm width, 10mm rise
Stem	Race Face Aeffect Alloy, 35mm clamp, 6 degree
Seatpost	Cervélo SP29 Carbon 30.9
Saddle	Prologo Dimension NDR Nack
Bottom Bracket	SRAM DUB, BSA 73mm
Headset	FSA IS2 1-1/2 x 1-1/2
Tires	Maxxis Rekon Race, EXO 120TPI, 29x2.4
Crankset	SRAM XX1 Eagle, 32T, Boost 148 DUB
Chain	SRAM XX1 Eagle, 12 speed
Cassette	SRAM XX1 Eagle, 10-52, 12 speed
Rear Derailleur	SRAM XX1 Eagle AXS, 12 speed
Max Tire Width (Actual)	60mm (2.4")
Shifters	SRAM AXS Rocker
Brake Calipers	SRAM Level Ultimate
Brake Levers	SRAM Level Ultimate
Wheels	Rear: Reserve 28 XC, 28mm IW, i9 1/1, 12x148mm, XD freehub, 24H, centerlock, tubeless compatible Front: Reserve 28 XC, 28mm IW, i9 1/1, 15x110mm, 24H, centerlock, tubeless compatible
Thru Axles	Cervelo Thru-axle, 12x148
Brake Rotor	SRAM CLX R Centerlock