

2026 Niner Air 9 - Frame - Technical Specifications

| | | | |
|--------------------------|--|-------------------------------|---|
| Rear suspension travel | n/a | Maximum front suspension | 120mm |
| Shock size | n/a | Shock mounting hardware | n/a |
| Suggested shock sag | n/a | Seatpost size | 30.9mm |
| Seat collar size | 34.9mm | Cable routing | external |
| Front derailleur type | 34.9 side swing, front pull | Headset size | 1.125" X 1.5" Tapered Integrated (Campy Style) Head Tube, Headset Included, Cane Creek Description: IS42/28.6 IS52/40 |
| Pivot bearing specs | n/a | Chainring compatibility | Compatible With Standard 1X, 2X And 3X Systems |
| Maximum chainring size | 1x max chain ring size: 34T - Boost Chainring Recommended | Q-Factor | 168mm |
| ISCG compatibility | no | Bottom bracket type | 73mm PF30 BB Shell (Adapters Required For BSA Type BBs); compatible with Biocentric 30 BB |
| Brake mount type | Post mount | Maximum rear rotor size | 180mm |
| Rear wheel spacing | Boost 148mm | Rear wheel through-axle spec | |
| Front wheel axle spacing | Boost 110mm | Front wheel through-axle spec | |
| Max tire size | 29x2.4 or 27.5x3.0 Tire (Tire Sizes Vary By Brand, Some Tires May Not Fit) | | |