

2026 Niner ORE 9 RDO - Frameset - Technical Specifications

| | | | |
|-------------------------------|--|--------------------------|---|
| FRAME FITTINGS AND MOUNTS | 2 INNER BOTTLE MOUNTS, 1 UNDER DOWNTUBE BOTTLE MOUNT, TOP TUBE BAG MOUNT | HEADSET SIZE | 1.125" X 1.5" TAPERED INTEGRATED HEAD TUBE, HEADSET INCLUDED, IS42/28.6 IS52/40 |
| SEATPOST CLAMP DIAMETER | 31.8MM | Q-FACTOR | 150MM |
| CHAINRING SIZE | 1X - 48T, 2X - 50/34T | BOTTOM BRACKET TYPE | T47 85.5MM SHELL WIDTH |
| ISCG COMPATIBILITY | NO | REAR WHEEL SPACING | 12X142MM |
| BIOCENTRIC 30 COMPATIBILITY | NO | FRONT WHEEL AXLE SPACING | 12X100MM |
| MAXIMUM BRAKE ROTOR SIZE | 160MM FRONT AND REAR | MAXIMUM TIRE SIZE | 700C X 50 OR 650B X 2.0 (TIRES VARY BY BRAND, SOME BRANDS MAY NOT FIT) |
| REAR WHEEL THROUGH AXLE SPEC | M12 X P1.0 X 174MM | FORK RAKE | 50MM |
| FRONT WHEEL THROUGH AXLE SPEC | M12 X P1.5 X 125MM | FORK AXLE TO CROWN | 435MM |
| CABLE ROUTING | FULL SLEEVE INTERNAL, DI2 COMPATIBLE, INTERNAL ROUTED DROPPER READY | SEATPOST DIAMETER | 27.2MM |