

2026 Niner RKT 9 RDO - Eagle 70 - Carbon/ Emerald - Technical Specifications

frame fittings and mounts	TWO BOTTLE CAGE MOUNTS PLUS ACCESSORY STORAGE MOUNTS ON TOP TUBE	Rear suspension travel	100mm
Maximum front suspension	120mm	fork offset	44mm
Shock size	165x40MM	Shock mounting hardware	UPPER – M10 X 54 TRUNNION; LOWER M8 X 25MM
Suggested shock sag	25% - moves the O-ring 9.5mm down the shaft	Seatpost size	30.9
Seat collar size	34.9	Cable routing	internal, full sleeve guides; Di2 compatible
Front derailleur	S3/ Low Direct Mount Front Derailleur	Headset size	1.125" X 1.5" Tapered Integrated (Campy Style) Head Tube, Headset Included, Cane Creek Description: IS42/28.6 IS52/40
Pivot bearing specs	Sealed Cartridge Enduro Max Black Oxide Bearings - (8x) 26x17x5	Chainring compatibility	SINGLE, 38T MAX
Maximum chainring size	1x max chain ring size = 38T - Boost Chainring Recommended	Q-Factor	168mm
ISCG compatibility	no	Bottom bracket type	BSA THREADED
Biocentric compatible?	no	Brake mount type	Post mount
Maximum rear rotor size	180mm	Rear wheel spacing	148x12mm
Rear wheel through-axle spec	M12x1.75Px182L	Front wheel axle spacing	110x15mm
Front wheel through-axle spec		Max tire size	29 X 2.5