

2026 Niner RLT 9 - Frameset - Black/Avalanche Grey - Technical Specifications

frame mounts and fittings	2 Inner Triangle Bottle Mounts, rack and fender mounts.	Rear suspension travel	n/a
Maximum front suspension	n/a	Fork rake	45mm
Shock size	n/a	Shock mounting hardware	n/a
Suggested shock sag	n/a	Seatpost size	27.2mm
Seat collar size	31.8mm	Cable routing	internal, Di2 compatible
Front derailleur type		Headset size	1.125" X 1.5" TAPERED INTEGRATED (CAMPY STYLE) HEAD TUBE, HEADSET INCLUDED, CANE CREEK DESCRIPTION: IS42/28.6 IS52/40
Pivot bearing specs	n/a	Chainring compatibility	Compatible With Standard 1X, 2X And 3X Systems
Maximum chainring size	n/a	Q-Factor	168mm
ISCG compatibility	no	Bottom bracket type	68MM PF30 BB SHELL (ADAPTORS REQUIRED FOR BSA TYPE BBs)
Biocentric 30 compatibility	yes	Brake mount type	flat mount (30mm rear)
Maximum rear rotor size	160mm	Rear wheel spacing	12x142mm
Rear wheel through-axle spec	M12 x 1.75P x 174L	Front wheel axle spacing	12x 100mm thru axle
Front wheel through-axle spec	M12 x 1.5P x 125L	Max tire size	700x50c or 650B x 2.0