

2026 Niner RLT 9 RDO - Frameset - Technical Specifications

| | | | |
|-------------------------------|---|--------------------------|---|
| frame mounts and fittings | 2 Inner Triangle Bottle Mounts, rack and fender mounts, accessory mounts on fork. | Rear suspension travel | n/a |
| Maximum front suspension | n/a | Fork rake | 45mm |
| Shock size | n/a | Shock mounting hardware | N/A |
| Suggested shock sag | n/a | Seatpost size | 27.2mm |
| Seat collar size | 31.8mm | Cable routing | Full Sleeve internal, Di2 compatible |
| Front derailleur type | | Headset size | 1.125" X 1.5" TAPERED INTEGRATED (CAMPY STYLE) HEAD TUBE, HEADSET INCLUDED, CANE CREEK DESCRIPTION: IS42/28.6 IS52/40 |
| Pivot bearing specs | n/a | Chainring compatibility | Compatible With Standard 1x and 2x systems |
| Maximum chainring size | 1x - 48T; 2x - 50/34T | Q-Factor | 168mm |
| ISCG compatibility | no | Bottom bracket type | 68MM PF30 BB SHELL (ADAPTORS REQUIRED FOR BSA TYPE BBs) |
| Biocentric 30 compatibility | yes | Brake mount type | flat mount (30mm rear) |
| Maximum rear rotor size | 160mm | Rear wheel spacing | 12x142mm |
| Rear wheel through-axle spec | M12 x 1.75P x 174L | Front wheel axle spacing | 12x 100mm thru axle |
| Front wheel through-axle spec | M12 x 1.5P x 125L | Max tire size | 700x50c or 650b x 2.0 (Tires vary by brand, some brands may not fit) |