


# 2026 Scott Spark RC SL Bike - Carbon Black - Geometry



## Geometrical Chart in MM

|   |                                                                     | S          | M          | L          | XL         |
|---|---------------------------------------------------------------------|------------|------------|------------|------------|
| A | head tube angle / angle tube de direction                           | 67.2 °     | 67.2 °     | 67.2 °     | 67.2 °     |
| B | head tube length / hauteur tube de direction                        | 90.0 mm    | 90.0 mm    | 105.0 mm   | 115.0 mm   |
| C | top tube horizontal / longueur horizontale tube supérieur           | 562.0 mm   | 590.0 mm   | 614.0 mm   | 642.0 mm   |
| D | standover height / hauteur entre-jambes                             | 758.0 mm   | 765.0 mm   | 776.0 mm   | 799.0 mm   |
| E | BB offset / deport axe de pédalier                                  | -45.0 mm   | -45.0 mm   | -45.0 mm   | -45.0 mm   |
| F | BB height / hauteur axe de pédalier                                 | 330.0 mm   | 330.0 mm   | 330.0 mm   | 330.0 mm   |
| G | wheel base / entraxe roues                                          | 1,129.0 mm | 1,159.0 mm | 1,190.0 mm | 1,231.0 mm |
| H | BB center to toptube center / dist. boîtier - milieu tube supérieur |            |            |            |            |

|   |                                                                     |          |          |          |          |
|---|---------------------------------------------------------------------|----------|----------|----------|----------|
| I | BB center to top of seattube / dist. boitier - sommet tube de selle | 415.0 mm | 440.0 mm | 490.0 mm | 540.0 mm |
| J | seat angle / angle tube de selle                                    | 75.9 °   | 76.1 °   | 76.6 °   | 76.9 °   |
| K | chainstay / longueur des bases                                      | 437.5 mm | 437.5 mm | 437.5 mm | 437.5 mm |
| L | reach / reach                                                       | 411.0 mm | 441.0 mm | 471.0 mm | 501.0 mm |
| M | stack / stack                                                       | 602.5 mm | 602.5 mm | 616.0 mm | 625.0 mm |
| N | stem length / longueur potence                                      | 50.0 mm  | 60.0 mm  | 70.0 mm  | 80.0 mm  |
| O | trail / chasse au sol                                               | 115.0 mm | 115.0 mm | 115.0 mm | 115.0 mm |
| P | fork length / longueur fourche                                      | 530.0 mm | 530.0 mm | 530.0 mm | 530.0 mm |
| Q | Maximum Seatpost Insertion / Insertion maximale de la tige de selle | 150.0 mm | 175.0 mm | 225.0 mm | 275.0 mm |
| R | Crank Length / longueur de manivelle                                | 170.0 mm | 170.0 mm | 175.0 mm | 175.0 mm |

## Geometrical Chart in Inches

|   |                                                                     | S       | M       | L       | XL      |
|---|---------------------------------------------------------------------|---------|---------|---------|---------|
| A | head tube angle / angle tube de direction                           | 67.2 °  | 67.2 °  | 67.2 °  | 67.2 °  |
| B | head tube length / hauteur tube de direction                        | 3.5 in  | 3.5 in  | 4.1 in  | 4.5 in  |
| C | top tube horizontal / longueur horizontale tube supérieur           | 22.1 in | 23.2 in | 24.2 in | 25.3 in |
| D | standover height / hauteur entre-jambes                             | 29.8 in | 30.1 in | 30.6 in | 31.5 in |
| E | BB offset / deport axe de pédalier                                  | -1.8 in | -1.8 in | -1.8 in | -1.8 in |
| F | BB height / hauteur axe de pédalier                                 | 13.0 in | 13.0 in | 13.0 in | 13.0 in |
| G | wheel base / entraxe roues                                          | 44.4 in | 45.6 in | 46.9 in | 48.5 in |
| H | BB center to toptube center / dist. boitier - milieu tube supérieur |         |         |         |         |
| I | BB center to top of seattube / dist. boitier - sommet tube de selle | 16.3 in | 17.3 in | 19.3 in | 21.3 in |
| J | seat angle / angle tube de selle                                    | 75.9 °  | 76.1 °  | 76.6 °  | 76.9 °  |
| K | chainstay / longueur des bases                                      | 17.2 in | 17.2 in | 17.2 in | 17.2 in |
| L | reach / reach                                                       | 16.2 in | 17.4 in | 18.5 in | 19.7 in |
| M | stack / stack                                                       | 23.7 in | 23.7 in | 24.3 in | 24.6 in |
| N | stem length / longueur potence                                      | 2.0 in  | 2.4 in  | 2.8 in  | 3.1 in  |
| O | trail / chasse au sol                                               | 4.5 in  | 4.5 in  | 4.5 in  | 4.5 in  |
| P | fork length / longueur fourche                                      | 20.9 in | 20.9 in | 20.9 in | 20.9 in |
| Q | Maximum Seatpost Insertion / Insertion maximale de la tige de selle | 5.9 in  | 6.9 in  | 8.9 in  | 10.8 in |
| R | Crank Length / longueur de manivelle                                | 6.7 in  | 6.7 in  | 6.9 in  | 6.9 in  |