



Type	S	M 27.5	M 29	L	XL	XXL
STACK (A)	599.3	604	629.3	634	638.5	643
REACH (B)	435	445	445	465	480	495
HEADTUBE ANGLE (C)	67.5°	67.5°	67°	67°	67°	67°
HEADTUBE LENGTH (D)	105	110	110	115	120	125
SEATTUBE ANGLE (EFFECTIVE) (E)	74.5°	74.5°	74.5°	74.5°	74.5°	74.5°
SEATTUBE LENGTH (F)	381	431	431	482	520	559
TOPTUBE (EFFECTIVE) (G)	601	612.5	619.5	640.8	657	673.3
BOTTOM BRACKET HEIGHT (H)	307	307	311.5	311.5	311.5	311.5
BOTTOM BRACKET DROP (I)	48	48	61	61	61	61
CHAINSTAY (J)	425	425	440	440	440	440
WHEELBASE (K)	1133.3	1145.2	1177.4	1199.3	1216.3	1233.2
STANDOVER HEIGHT (L)	659.07	705.48	714.04	744.93	774.59	807.84
FORK OFFSET (M)	44	44	51	51	51	51
SEATPOST DIAMETER	30.9	30.9	30.9	30.9	30.9	30.9
HANDLEBAR WIDTH	780	780	780	780	780	780
STEM LENGTH	45	45	45	45	45	45
CRANK LENGTH	170	175	175	175	175	175

All lengths in Millimeters