



| Type | XS | S | M 27.5 | M 29 | L | XL | XXL |
|--------------------------------|--------|--------|--------|--------|--------|--------|--------|
| STACK (A) | 580.8 | 585.5 | 590 | 616 | 620.5 | 625 | 630 |
| REACH (B) | 400 | 415 | 430 | 430 | 445 | 465 | 475 |
| HEADTUBE ANGLE (C) | 68.5° | 68.5° | 68.5° | 68° | 68° | 68° | 68° |
| HEADTUBE LENGTH (D) | 100 | 105 | 110 | 110 | 115 | 120 | 125 |
| SEATTUBE ANGLE (EFFECTIVE) (E) | 74° | 74° | 74° | 74° | 74° | 74° | 74° |
| SEATTUBE LENGTH (F) | 330 | 381 | 431 | 431 | 481 | 520 | 559 |
| TOPTUBE (EFFECTIVE) (G) | 566.5 | 583 | 599.2 | 606.6 | 623 | 644.2 | 655.6 |
| BOTTOM BRACKET HEIGHT (H) | 307 | 307 | 307 | 311.5 | 311.5 | 311.5 | 311.5 |
| BOTTOM BRACKET DROP (I) | 48 | 48 | 48 | 61 | 61 | 61 | 61 |
| CHAINSTAY (J) | 430 | 430 | 430 | 455 | 455 | 455 | 455 |
| WHEELBASE (K) | 1084.5 | 1101.3 | 1118.2 | 1160 | 1177 | 1199 | 1210 |
| STANDOVER HEIGHT (L) | 649.11 | 663.03 | 706.24 | 716.44 | 744.89 | 773.66 | 806.58 |
| FORK OFFSET (M) | 44 | 44 | 44 | 51 | 51 | 51 | 51 |
| SEATPOST DIAMETER | 27.2 | 27.2 | 27.2 | 27.2 | 27.2 | 27.2 | 27.2 |
| HANDLEBAR WIDTH | 780 | 780 | 780 | 780 | 780 | 780 | 780 |
| STEM LENGTH | 45 | 45 | 45 | 45 | 45 | 45 | 45 |
| CRANK LENGTH | 170 | 170 | 175 | 175 | 175 | 175 | 175 |

All lengths in Millimeters