

# BULLIT 90

## Sizing & Geometry

### Find your size

If you're on the cusp between the recommended height range of two sizes, the absolute best thing is to try to ride them both. At a minimum, check the stack/reach measurements on your current bike and compare it to the new model you are looking at to get an idea of a fit you are already comfortable with. If riding the bike is not an option, consider the following.

### Personal Preference

A larger size frame will be more stable, and will give you more room to move without upsetting the weight-balance of the bike. The larger size will put the front wheel further in front of you, which gives the feeling of security and conversely, it will require more significant body movements when you WANT to shift the weight-bias of the bike. Think hard about your riding style and how active/intuitive you want it to be vs stable and speedy. You'll need to work a bit harder to muscle the larger bike around.

### Body Dimension

Not all bodies at a given height are the same. If you have longer legs and a shorter torso than the average person your height, that may push you towards the smaller of the recommended sizes. If you're all torso and arms, most likely you'll want to size up.

### Bike Geometry

	s	m	l	xl	xxl
Reach (Hi/Lo)	435/432	460/457	480/477	500/497	525/522
Stack (Hi/Lo)	622/625	631/635	640/643	654/656	670/674
Head Tube Angle (Hi/Lo)	63.6/63.3	63.6/63.3	63.6/63.3	63.6/63.3	63.6/63.3
Head Tube Length	100	110	120	135	155
Rear Center	440	443	446	449	452
Front Center	780	809	834	860	894
BB Height (Hi/Lo)	346/342	346/342	346/342	346/342	346/342
BB Drop Front (Hi/Lo)	27/31	27/31	27/31	27/31	27/31
BB Drop Rear (Hi/Lo)	9/13	9/13	9/13	9/13	9/13
Wheelbase	1220	1252	1280	1309	1346
Top Tube Length	571	596	617	640	670
Seat Tube Length	380	400	420	460	500
Seat Tube Angle (Hi/Lo)	78.6/78.3	78.7/78.4	78.7/78.4	78.7/78.4	78.6/78.3
Standover Height (Hi/Lo)	745/740	739/735	738/733	738/733	735/730

All units are in millimeters or degrees.