


G23 7C Carbon Fiber Wheelset

RIM Specs

Details	Front	Rear
Rim Depth	25mm	25mm
External Width	31.5mm	31.5mm
Internal Width	23mm	23mm
Hole Count	24	24
Effective Rim Diameter	608mm	608mm
Optimized Tire Sizes	33c - 45c	33c - 45c
Accepted Tire Sizes	28c - 50c	28c - 50c



WHEELSET Specs

Details	Front	Rear	Wheelset
Rim Weight	329g	329g	658g
ENVE Alloy	591g	715g	1305g
i9 Torch Road CL	574g	714g	1287g
Chris King R45 CL	599g	718g	1316g

SPOKE INFORMATION

Details	Spoke Cross	Front Length (NDS/DS)	Rear Length (NDS/DS)
ENVE Alloy	2X	294mm / 296mm	296mm / 294mm
DT 240 CL	2X	294mm / 296mm	294mm / 292mm
Chris King R45 CL	2X	290mm / 292mm	292mm / 290mm
i9 Torch Classic	2X	294mm / 294mm	296mm / 290mm

Note: *This wheelset is built with Sapim CX Ray spokes. Those built before May 2018 may use a DT Swiss spoke equivalent. DT Swiss spoke heads are stamped "DT".

PRESSURE RECOMMENDATIONS- PSI

Rider Weight	Rim Model	M50				G23				G27			SES 4.5 AR. M525			
	Inner Rim Width	21mm				23mm				27mm			25mm			
		28-30mm	32-35mm	42-45mm	28-30mm	32-35mm	35-38mm	38-42mm	42-45mm	38-42mm	42-45mm	47-55mm 1.95-2.1"	28-30mm	32-35mm	38-42mm	42-45mm
90 lbs./ 41Kg	27	24	19	26	23	22	20	18	20	17	13	25	23	20	17	13
100 lbs./ 45Kg	30	27	20	28	25	24	22	19	22	19	14	28	25	22	19	14
110 lbs./ 50Kg	32	29	22	31	27	26	24	21	24	21	15	30	27	23	20	15

Rider Weight	Rim Model	M50				G23					G27			SES 4.5 AR. M525			
	Inner Rim Width	21mm				23mm					27mm			25mm			
		28-30mm	32-35mm	42-45mm	28-30mm	32-35mm	35-38mm	38-42mm	42-45mm	38-42mm	42-45mm	47-55mm 1.95-2.1"	28-30mm	32-35mm	38-42mm	42-45mm	47-55mm 1.95-2.1"
120 lbs./ 54Kg	35	31	24	33	29	28	26	23	25	22	17	32	29	25	22	16	
130 lbs./ 59Kg	37	33	25	35	32	30	28	24	27	24	18	34	31	27	24	18	
140 lbs./ 64Kg	39	35	27	37	34	32	29	26	29	25	19	37	33	29	25	19	
150 lbs./ 64Kg	42	37	29	40	36	34	31	27	31	27	20	39	35	30	27	20	
160 lbs./ 73Kg	44	39	30	42	37	36	33	29	32	28	21	41	37	32	28	21	
170 lbs./ 77Kg	46	41	32	44	39	37	34	30	34	30	22	43	38	34	29	22	
180 lbs./ 82Kg	48	43	33	46	41	39	36	31	35	31	23	45	40	35	31	23	
190 lbs./ 86Kg	50	45	34	47	42	40	37	33	37	32	24	46	42	36	32	24	
200 lbs./ 91 Kg	51	46	35	49	44	42	38	34	38	33	25	48	43	37	33	24	
210 lbs./ 91Kg	53	47	36	50	45	43	39	34	39	34	25	49	44	38	34	25	
220 lbs./ 100Kg	54	48	37	51	46	44	40	35	40	35	26	50	45	39	34	26	
230 lbs./ 104Kg	55	49	38	52	47	44	41	36	40	35	26	51	46	40	35	26	
240 lbs./ 109 Kg	55	50	38	53	47	45	41	36	41	36	27	51	46	40	35	26	
250 lbs./ 113Kg	56	50	38	53	47	45	41	36	41	36	27	52	46	41	36	26	

PRESSURE RECOMMENDATIONS- BAR

Rider Weight	Rim Model	M50				G23				G27			SES 4.5 AR. M525			
	Inner Rim Width	21mm				23mm				27mm			25mm			
	28-30mm	32-35mm	42-45mm	28-30mm	32-35mm	35-38mm	38-42mm	42-45mm	38-42mm	42-45mm	47-55mm 1.95-2.1"	28-30mm	32-35mm	38-42mm	42-45mm	47-55mm 1.95-2.1"
90 lbs./ 41Kg	1.88	1.69	1.29	1.78	1.60	1.52	1.40	1.23	1.38	1.21	0.90	1.74	1.56	1.37	1.20	0.89
100 lbs./ 45Kg	2.05	1.84	1.41	1.94	1.74	1.66	1.52	1.34	1.50	1.31	0.98	1.90	1.70	1.49	1.30	0.97
110 lbs./ 50Kg	2.21	1.99	1.52	2.10	1.89	1.80	1.65	1.45	1.62	1.42	1.06	2.06	1.84	1.61	1.41	1.05
120 lbs./ 54Kg	2.38	2.14	1.64	2.26	2.03	1.93	1.78	1.56	1.75	1.53	1.14	2.21	1.99	1.74	1.52	1.13
130 lbs./ 59Kg	2.55	2.29	1.76	2.42	2.18	2.07	1.90	1.67	1.87	1.64	1.22	2.37	2.13	1.86	1.63	1.21
140 lbs./ 64Kg	2.72	2.44	1.87	2.58	2.32	2.20	2.03	1.77	1.99	1.75	1.30	2.52	2.26	1.98	1.73	1.29
150 lbs./ 68Kg	2.88	2.58	1.98	2.73	2.45	2.33	2.15	1.88	2.11	1.85	1.38	2.67	2.40	2.10	1.84	1.37
160 lbs./ 73Kg	3.03	2.72	2.08	2.88	2.58	2.46	2.26	1.98	2.22	1.95	1.45	2.81	2.53	2.21	1.93	1.44
170 lbs./ 77Kg	3.18	2.85	2.18	3.02	2.71	2.58	2.37	2.07	2.33	2.04	1.52	2.95	2.65	2.31	2.03	1.51
180 lbs./ 82Kg	3.31	2.97	2.28	3.15	2.82	2.68	2.47	2.16	2.43	2.13	1.59	3.07	2.76	2.41	2.11	1.58
190 lbs./ 86Kg	3.44	3.08	2.36	3.26	2.93	2.78	2.56	2.24	2.52	2.21	1.65	3.19	2.86	2.50	2.19	1.63
200 lbs./ 91 Kg	3.55	3.18	2.44	3.37	3.02	2.87	2.64	2.32	2.60	2.28	1.70	3.29	2.95	2.58	2.26	1.69
210 lbs./ 91Kg	3.64	3.27	2.50	3.46	3.10	2.95	2.71	2.38	2.67	2.34	1.74	3.38	3.03	2.65	2.32	1.73
220 lbs./ 100Kg	3.72	3.34	2.56	3.53	3.17	3.01	2.77	2.43	2.73	2.39	1.78	3.45	3.10	2.71	2.37	1.77
230 lbs./ 104Kg	3.78	3.39	2.60	3.59	3.22	3.06	2.82	2.47	2.77	2.43	1.81	3.51	3.15	2.75	2.41	1.80
240 lbs./ 109 Kg	3.82	3.43	2.63	3.63	3.26	3.10	2.85	2.49	2.80	2.45	1.83	3.54	3.18	2.78	2.44	1.82
250 lbs./ 113Kg	3.84	3.45	2.64	3.64	3.27	3.11	2.86	2.51	2.81	2.46	1.84	3.56	3.20	2.79	2.45	1.83

Recommended Max Tire Pressure for Given Rim & Tire Volume Combo on Gravel Road Surfaces

Note: Tire pressures are intended as a starting recommendation based on the listed wheel being set up with tubeless tire.

The pressure value is calculated considering a tubeless set up, intended road surface, rider's weight, average bike weight, inner rim width, and tire volume.