



Size	A : Stack	B : Reach	C : Wheel Size	D : Head Tube Angle	E : Trail *	F : Fork Offset	G : Head Tube Length	H : Bottom Bracket Drop	I : Front Center	J : Rear Center	K : Wheelbase	L : Standover Height
S	468 mm (18.43 ")	386 mm (15.20 ")	700c	71°	61.4 mm (2.42 ")	53 mm (2.09 ")	76 mm (2.99 ")	75 mm (2.95 ")	582 mm (22.91 ")	405 mm (15.94 ")	975 mm (38.39 ")	689 mm (27.13 ")
M	496 mm (19.53 ")	404 mm (15.91 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	97 mm (3.82 ")	75 mm (2.95 ")	587 mm (23.11 ")	405 mm (15.94 ")	980 mm (38.58 ")	702 mm (27.64 ")
L	524 mm (20.63 ")	423 mm (16.65 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	126 mm (4.96 ")	75 mm (2.95 ")	614 mm (24.17 ")	405 mm (15.94 ")	1008 mm (39.69 ")	746 mm (29.37 ")

Size	A : Stack	B : Reach	C : Wheel Size	D : Head Tube Angle	E : Trail *	F : F ork Offset	G : Head Tube Length	H : Bottom Bracket Drop	I : Front Center	J : Rear Center	K : Wheelbase	L : Standover Height
XL	552 mm (21.73 ")	442 mm (17.40 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	156 mm (6.14 ")	75 mm (2.95 ")	642 mm (25.28 ")	405 mm (15.94 ")	1035 mm (40.75 ")	775 mm (30.51 ")