

ASPECT

Geometry Chart (MM)

| | | XS | S | M | L | XL | XXL |
|---|------------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|
| A | HEAD TUBE ANGLE | 68.5 ° | 68.5 ° | 68.5 ° | 68.5 ° | 68.5 ° | 68.5 ° |
| В | HEAD TUBE LENGTH | 95.0 MM | 100.0 MM | 110.0 MM | 120.0 MM | 135.0 MM | 150.0 MM |
| С | TOP TUBE HORIZONTAL | 560.0 MM | 585.0 MM | 600.0 MM | 615.0 MM | 635.0 MM | 655.0 MM |
| D | STANDOVER HEIGHT | 743.0 MM | 771.0 MM | 783.0 MM | 821.0 MM | 857.0 MM | 891.0 MM |
| E | BB OFFSET | -60.0 MM | -60.0 MM | -60.0 MM | -60.0 MM | -60.0 MM | -60.0 MM |
| F | BB HEIGHT | 316.0 MM | 316.0 MM | 316.0 MM | 316.0 MM | 316.0 MM | 316.0 MM |
| G | WHEEL BASE | 1,102.0 MM | 1,090.0 MM | 1,102.0 MM | 1,123.0 MM | 1,144.0 MM | 1,164.0 MM |
| Н | BB CENTER TO TOPTUBE CENTER | 309.0 MM | 349.0 MM | 394.0 MM | 434.0 MM | 484.0 MM | 534.0 MM |
| I | BB CENTER TO TOP OF SEATTUBE | 355.0 MM | 395.0 MM | 440.0 MM | 480.0 MM | 530.0 MM | 580.0 MM |
| J | SEAT ANGLE | 73.5 ° | 73.5 ° | 73.5 ° | 73.5 ° | 73.5 ° | 73.5 ° |
| K | CHAINSTAY | 450.0 MM | 450.0 MM | 450.0 MM | 450.0 MM | 450.0 MM | 450.0 MM |
| L | REACH | 388.0 MM | 406.0 MM | 419.0 MM | 431.0 MM | 447.0 MM | 463.0 MM |
| M | STACK | 580.0 MM | 603.0 MM | 612.0 MM | 622.0 MM | 636.0 MM | 649.0 MM |
| N | STEM LENGTH | 50.0 MM | 60.0 MM | 70.0 MM | 80.0 MM | 90.0 MM | 100.0 MM |

Geometry Chart (INCHES)

| | | XS | S | M | L | XL | XXL |
|----|---------------------|--------|--------|--------|--------|--------|--------|
| ΙΔ | HEAD TUBE ANGLE | 68.5 ° | 68.5 ° | 68.5 ° | 68.5 ° | 68.5 ° | 68.5 ° |
| В | HEAD TUBE LENGTH | 3.7 IN | 3.9 IN | 4.3 IN | 4.7 IN | 5.3 IN | 5.9 IN |
| | TOP TUBE | | | | | | |

| C | HORIZONTAL | 22.0 IN | 23.0 IN | 23.6 IN | 24.2 IN | 25.0 IN | 25.8 IN |
|---|------------------------------------|---------|---------|---------|---------|---------|---------|
| D | STANDOVER HEIGHT | 29.3 IN | 30.4 IN | 30.8 IN | 32.3 IN | 33.7 IN | 35.1 IN |
| E | BB OFFSET | -2.4 IN |
| F | BB HEIGHT | 12.4 IN |
| G | WHEEL BASE | 43.4 IN | 42.9 IN | 43.4 IN | 44.2 IN | 45.0 IN | 45.8 IN |
| Н | BB CENTER TO TOPTUBE CENTER | 12.2 IN | 13.7 IN | 15.5 IN | 17.1 IN | 19.1 IN | 21.0 IN |
| I | BB CENTER TO TOP OF SEATTUBE | 14.0 IN | 15.6 IN | 17.3 IN | 18.9 IN | 20.9 IN | 22.8 IN |
| J | SEAT ANGLE | 73.5 ° | 73.5 ° | 73.5 ° | 73.5 ° | 73.5 ° | 73.5 ° |
| K | CHAINSTAY | 17.7 IN |
| L | REACH | 15.3 IN | 16.0 IN | 16.5 IN | 17.0 IN | 17.6 IN | 18.2 IN |
| M | STACK | 22.8 IN | 23.7 IN | 24.1 IN | 24.5 IN | 25.0 IN | 25.6 IN |
| N | STEM LENGTH | 2.0 IN | 2.4 IN | 2.8 IN | 3.1 IN | 3.5 IN | 3.9 IN |