



CONTESSA ACTIVE

SCOTT CONTESSA ACTIVE 50 PETROL BIKE Geometry Chart (INCHES)

		XS / 700	S / 700	M / 900	L / 900
A	HEAD TUBE ANGLE	68.0 \diamond	68.0 \diamond	68.5 \diamond	68.5 \diamond
B	HEAD TUBE LENGTH	3.7 IN	3.9 IN	4.3 IN	4.7 IN
C	TOP TUBE HORIZONTAL	22.0 IN	23.0 IN	23.6 IN	24.2 IN
D	STANDOVER HEIGHT	26.7 IN	27.7 IN	29.5 IN	30.6 IN
E	BB OFFSET	-1.7 IN	-1.7 IN	-2.4 IN	-2.4 IN
F	BB HEIGHT	12.1 IN	12.1 IN	12.4 IN	12.4 IN
G	WHEEL BASE	42.8 IN	43.9 IN	43.4 IN	44.2 IN
H	BB CENTER TO TOPTUBE CENTER	12.2 IN	13.4 IN	15.4 IN	17.0 IN
I	BB CENTER TO TOP OF SEATTUBE	14.0 IN	15.6 IN	17.3 IN	18.9 IN
J	SEAT ANGLE	74.0 \diamond	74.0 \diamond	73.5 \diamond	73.5 \diamond
K	CHAINSTAY	17.1 IN	17.1 IN	17.7 IN	17.7 IN
L	REACH	15.8 IN	16.5 IN	16.5 IN	17.0 IN
M	STACK	21.7 IN	22.6 IN	24.1 IN	24.5 IN
N	STEM LENGTH	2.0 IN	2.0 IN	2.4 IN	2.4 IN

SCOTT CONTESSA ACTIVE 50 PETROL BIKE Geometry Chart (MM)

		XS / 700	S / 700	M / 900	L / 900
A	HEAD TUBE ANGLE	68.0 \diamond	68.0 \diamond	68.5 \diamond	68.5 \diamond
B	HEAD TUBE LENGTH	95.0 MM	100.0 MM	110.0 MM	120.0 MM

C	TOP TUBE HORIZONTAL	560.0 MM	585.0 MM	600.0 MM	615.0 MM
D	STANDOVER HEIGHT	678.0 MM	704.0 MM	750.0 MM	777.0 MM
E	BB OFFSET	-44.0 MM	-44.0 MM	-60.0 MM	-60.0 MM
F	BB HEIGHT	308.5 MM	308.5 MM	316.0 MM	316.0 MM
G	WHEEL BASE	1,087.0 MM	1,115.0 MM	1,102.0 MM	1,123.0 MM
H	BB CENTER TO TOPTUBE CENTER	311.0 MM	341.0 MM	391.0 MM	431.0 MM
I	BB CENTER TO TOP OF SEATTUBE	355.0 MM	395.0 MM	440.0 MM	480.0 MM
J	SEAT ANGLE	74.0 °	74.0 °	73.5 °	73.5 °
K	CHAINSTAY	435.0 MM	435.0 MM	450.0 MM	450.0 MM
L	REACH	402.0 MM	420.0 MM	419.0 MM	431.0 MM
M	STACK	552.0 MM	575.0 MM	612.0 MM	622.0 MM
N	STEM LENGTH	50.0 MM	50.0 MM	60.0 MM	60.0 MM