



Geometry Chart (MM)

		S / 900	M / 900	L / 900	XL / 900
A	HEAD TUBE ANGLE (+0.6° HEADSET SETTING)	67.9 °	67.9 °	67.9 °	67.9 °
B	HEAD TUBE LENGTH	90.0 MM	95.0 MM	110.0 MM	120.0 MM
C	TOP TUBE HORIZONTAL	575.0 MM	600.2 MM	626.0 MM	656.5 MM
D	STANDOVER HEIGHT	752.0 MM	781.0 MM	800.0 MM	835.1 MM
E	BB OFFSET	-62.0 MM	-62.0 MM	-62.0 MM	-62.0 MM
F	BB HEIGHT	313.0 MM	313.0 MM	313.0 MM	313.0 MM
G	WHEEL BASE	1,105.4 MM	1,131.1 MM	1,158.0 MM	1,189.4 MM
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	390.0 MM	440.0 MM	480.0 MM	530.0 MM
J	SEAT ANGLE	75.4 °	75.4 °	75.3 °	75.3 °
K	CHAINSTAY	425.0 MM	425.0 MM	425.0 MM	425.0 MM
L	REACH	418.5 MM	442.3 MM	463.6 MM	491.2 MM
M	STACK	600.3 MM	604.9 MM	618.9 MM	628.1 MM
N	STEM LENGTH	50.0 MM	60.0 MM	70.0 MM	80.0 MM
O	TRAIL	105.1 MM	105.0 MM	105.0 MM	105.0 MM

Geometry Chart (INCHES)

		S / 900	M / 900	L / 900	XL / 900
A	HEAD TUBE ANGLE (+0.6° HEADSET SETTING)	67.9 °	67.9 °	67.9 °	67.9 °

B	HEAD TUBE LENGTH	3.5 IN	3.7 IN	4.3 IN	4.7 IN
C	TOP TUBE HORIZONTAL	22.6 IN	23.6 IN	24.6 IN	25.8 IN
D	STANDOVER HEIGHT	29.6 IN	30.7 IN	31.5 IN	32.9 IN
E	BB OFFSET	-2.4 IN	-2.4 IN	-2.4 IN	-2.4 IN
F	BB HEIGHT	12.3 IN	12.3 IN	12.3 IN	12.3 IN
G	WHEEL BASE	43.5 IN	44.5 IN	45.6 IN	46.8 IN
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	15.4 IN	17.3 IN	18.9 IN	20.9 IN
J	SEAT ANGLE	75.4 °	75.4 °	75.3 °	75.3 °
K	CHAINSTAY	16.7 IN	16.7 IN	16.7 IN	16.7 IN
L	REACH	16.5 IN	17.4 IN	18.3 IN	19.3 IN
M	STACK	23.6 IN	23.8 IN	24.4 IN	24.7 IN
N	STEM LENGTH	2.0 IN	2.4 IN	2.8 IN	3.1 IN
O	TRAIL	4.1 IN	4.1 IN	4.1 IN	4.1 IN