



SCALE: 950, 960, 965, 970, 980

EN						
A	head tube angle	69.5 °				
B	head tube length	100.0 mm	100.0 mm	115.0 mm	125.0 mm	135.0 mm
C	top tube horizontal	575.0 mm	600.0 mm	620.0 mm	640.0 mm	660.0 mm
D	standover height	748.0 mm	776.0 mm	805.0 mm	840.0 mm	874.0 mm
E	BB offset	-58.0 mm	-58.0 mm	-58.0 mm	-58.0 mm	-58.0 mm
F	BB height	312.0 mm	312.0 mm	312.0 mm	312.0 mm	312.0 mm
G	wheel base	1,092.1 mm	1,118.0 mm	1,138.2 mm	1,159.0 mm	1,120.0 mm
I	BB center to top of seattube	390.0 mm	440.0 mm	480.0 mm	530.0 mm	580.0 mm
J	seat angle	73.6 °				
K	chainstay	440.0 mm	440.0 mm	440.0 mm	440.0 mm	440.0 mm
L	reach	396.8 mm	421.8 mm	437.7 mm	455.0 mm	492.2 mm
M	stack	605.3 mm	605.3 mm	619.4 mm	628.7 mm	638.1 mm
N	stem length	60.0 mm				
A	head tube angle	69.5 °				
B	head tube length	3.9 in	3.9 in	4.5 in	4.9 in	5.3 in
C	top tube horizontal	22.6 in	23.6 in	24.4 in	25.2 in	26.0 in
D	standover height	29.4 in	30.6 in	31.7 in	33.1 in	34.4 in
E	BB offset	-2.3 in	-2.3 in	-2.3 in	-2.3 in	-2.3 in
F	BB height	12.3 in	12.3 in	12.3 in	12.3 in	12.3 in
G	wheel base	43.0 in	44.0 in	44.8 in	45.6 in	44.1 in
I	BB center to top of seattube	15.4 in	17.3 in	18.9 in	20.9 in	22.8 in
J	seat angle	73.6 °				
K	chainstay	17.3 in	17.3 in	17.3 in	17.3 in	17.3 in
L	reach	15.6 in	16.6 in	17.2 in	17.9 in	19.4 in

M	stack	23.8 in	23.8 in	24.4 in	24.8 in	25.1 in
N	stem length		2.4 in			