



Geometry Chart (MM)

		S	M	L	XL
A	HEAD TUBE ANGLE	65.8 °	65.8 °	65.8 °	65.8 °
B	HEAD TUBE LENGTH	90.0 MM	90.0 MM	105.0 MM	115.0 MM
C	TOP TUBE HORIZONTAL	561.0 MM	589.0 MM	613.0 MM	641.0 MM
D	STANDOVER HEIGHT	759.0 MM	767.0 MM	778.0 MM	801.0 MM
E	BB OFFSET	-43.5 MM	-43.5 MM	-43.5 MM	-43.5 MM
F	BB HEIGHT	331.5 MM	331.5 MM	331.5 MM	331.5 MM
G	WHEEL BASE	1,145.0 MM	1,174.0 MM	1,205.0 MM	1,236.0 MM
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	415.0 MM	440.0 MM	490.0 MM	540.0 MM
J	SEAT ANGLE	75.7 °	75.9 °	76.4 °	76.7 °
K	CHAINSTAY	437.5 MM	437.5 MM	437.5 MM	437.5 MM
L	REACH	410.0 MM	440.0 MM	470.0 MM	500.0 MM
M	STACK	607.5 MM	607.5 MM	617.7 MM	627.0 MM
N	STEM LENGTH	50.0 MM	60.0 MM	60.0 MM	70.0 MM
O	TRAIL	107.0 MM	107.0 MM	107.0 MM	107.0 MM
P	FORK LENGTH	540.0 MM	540.0 MM	540.0 MM	540.0 MM
Q	MAXIMUM SEATPOST INSERTION	150.0 MM	175.0 MM	225.0 MM	275.0 MM
R	CRANK LENGTH	170.0 MM	175.0 MM	175.0 MM	175.0 MM

Geometry Chart (INCHES)

		S	M	L	XL
A	HEAD TUBE ANGLE	65.8 °	65.8 °	65.8 °	65.8 °
B	HEAD TUBE LENGTH	3.5 IN	3.5 IN	4.1 IN	4.5 IN
C	TOP TUBE HORIZONTAL	22.1 IN	23.2 IN	24.1 IN	25.2 IN

D	STANDOVER HEIGHT	29.9 IN	30.2 IN	30.6 IN	31.5 IN
E	BB OFFSET	-1.7 IN	-1.7 IN	-1.7 IN	-1.7 IN
F	BB HEIGHT	13.1 IN	13.1 IN	13.1 IN	13.1 IN
G	WHEEL BASE	45.1 IN	46.2 IN	47.4 IN	48.7 IN
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	16.3 IN	17.3 IN	19.3 IN	21.3 IN
J	SEAT ANGLE	75.7 °	75.9 °	76.4 °	76.7 °
K	CHAINSTAY	17.2 IN	17.2 IN	17.2 IN	17.2 IN
L	REACH	16.1 IN	17.3 IN	18.5 IN	19.7 IN
M	STACK	23.9 IN	23.9 IN	24.3 IN	24.7 IN
N	STEM LENGTH	2.0 IN	2.4 IN	2.4 IN	2.8 IN
O	TRAIL	4.2 IN	4.2 IN	4.2 IN	4.2 IN
P	FORK LENGTH	21.3 IN	21.3 IN	21.3 IN	21.3 IN
Q	MAXIMUM SEATPOST INSERTION	5.9 IN	6.9 IN	8.9 IN	10.8 IN
R	CRANK LENGTH	6.7 IN	6.9 IN	6.9 IN	6.9 IN