



Geometry Chart (MM)

		S	M	L	XL
A	HEAD TUBE ANGLE	67.2 °	67.2 °	67.2 °	67.2 °
B	HEAD TUBE LENGTH	90.0 MM	90.0 MM	105.0 MM	115.0 MM
C	TOP TUBE HORIZONTAL	562.0 MM	590.0 MM	614.0 MM	642.0 MM
D	STANDOVER HEIGHT	758.0 MM	765.0 MM	776.0 MM	799.0 MM
E	BB OFFSET	-45.0 MM	-45.0 MM	-45.0 MM	-45.0 MM
F	BB HEIGHT	330.0 MM	330.0 MM	330.0 MM	330.0 MM
G	WHEEL BASE	1,129.0 MM	1,159.0 MM	1,190.0 MM	1,231.0 MM
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	415.0 MM	440.0 MM	490.0 MM	540.0 MM
J	SEAT ANGLE	75.9 °	76.1 °	76.6 °	76.9 °
K	CHAINSTAY	437.5 MM	437.5 MM	437.5 MM	437.5 MM
L	REACH	411.0 MM	441.0 MM	471.0 MM	501.0 MM
M	STACK	602.5 MM	602.5 MM	616.0 MM	625.0 MM
N	STEM LENGTH	50.0 MM	60.0 MM	70.0 MM	80.0 MM
O	TRAIL	115.0 MM	115.0 MM	115.0 MM	115.0 MM
P	FORK LENGTH	530.0 MM	530.0 MM	530.0 MM	530.0 MM
Q	MAXIMUM SEATPOST INSERTION	150.0 MM	175.0 MM	225.0 MM	275.0 MM
R	CRANK LENGTH	170.0 MM	175.0 MM	175.0 MM	175.0 MM

Geometry Chart (INCHES)

--	--	--	--	--	--

		S	M	L	XL
A	HEAD TUBE ANGLE	67.2 °	67.2 °	67.2 °	67.2 °
B	HEAD TUBE LENGTH	3.5 IN	3.5 IN	4.1 IN	4.5 IN
C	TOP TUBE HORIZONTAL	22.1 IN	23.2 IN	24.2 IN	25.3 IN
D	STANDOVER HEIGHT	29.8 IN	30.1 IN	30.6 IN	31.5 IN
E	BB OFFSET	-1.8 IN	-1.8 IN	-1.8 IN	-1.8 IN
F	BB HEIGHT	13.0 IN	13.0 IN	13.0 IN	13.0 IN
G	WHEEL BASE	44.4 IN	45.6 IN	46.9 IN	48.5 IN
H	BB CENTER TO TOPTUBE CENTER				
I	BB CENTER TO TOP OF SEATTUBE	16.3 IN	17.3 IN	19.3 IN	21.3 IN
J	SEAT ANGLE	75.9 °	76.1 °	76.6 °	76.9 °
K	CHAINSTAY	17.2 IN	17.2 IN	17.2 IN	17.2 IN
L	REACH	16.2 IN	17.4 IN	18.5 IN	19.7 IN
M	STACK	23.7 IN	23.7 IN	24.3 IN	24.6 IN
N	STEM LENGTH	2.0 IN	2.4 IN	2.8 IN	3.1 IN
O	TRAIL	4.5 IN	4.5 IN	4.5 IN	4.5 IN
P	FORK LENGTH	20.9 IN	20.9 IN	20.9 IN	20.9 IN
Q	MAXIMUM SEATPOST INSERTION	5.9 IN	6.9 IN	8.9 IN	10.8 IN
R	CRANK LENGTH	6.7 IN	6.9 IN	6.9 IN	6.9 IN