



Size	47	51	54	57	60
Rider Height CM	<168	166-174	172-180	178-188	>186
Top Tube MM (tt)	518	534	549	564	583
Wheelbase MM (wb)	971	975	985	1001	1020
Seat Angle (sa)	73.5	73.5	73.5	73.5	73.5
Seatpost Length MM	350	350	350	350	350
Stack MM	515	539	559	583	610
Trail MM (trail)	76	66	63	63	63
Rear Center MM (rc)	410	410	410	410	410
Reach MM (reach)	365	374	383	391	402
Head Tube MM (ht)	118	138	157	182	210
Head Angle (ha)	70.5	72	72.5	72.5	72.5
BB Drop MM (drop)	69	69	69	69	69
Stem Length MM	90	100	110	120	120
Seat Tube MM (st)	442	505	535	565	600
Stem Angle	± 8	± 8	± 8	± 8	± 8
Post Offset MM	15	15	15	15	15
Crank Length MM	170	170	172.5	172.5	175
Fork Rake MM (fr)	41.6	41.6	41.6	41.6	41.6
Front Center MM (fc)	571	575	585	601	620
Fork Length MM (fl)	369	369	369	369	369
Bar Width MM	420	420	420	440	440
Bar Reach MM	70	70	70	70	70
Bar Drop MM	125	125	125	125	125