



| Type                           | S     | M     | L     | XL    |
|--------------------------------|-------|-------|-------|-------|
| STACK (A)                      | 626.5 | 626.5 | 635.8 | 658.6 |
| REACH (B)                      | 415   | 435   | 462.2 | 475.8 |
| HEADTUBE ANGLE (C)             | 66.5° | 66.5° | 66.5° | 66.5° |
| HEADTUBE LENGTH (D)            | 90    | 90    | 100   | 125   |
| SEATTUBE ANGLE (EFFECTIVE) (E) | 73.5° | 73.5° | 73.5° | 73.5° |
| SEATTUBE LENGTH (F)            | 390   | 420   | 465   | 525   |
| TOPTUBE (EFFECTIVE) (G)        | 575   | 595   | 620   | 637.6 |
| BOTTOM BRACKET HEIGHT (H)      | 336   | 336   | 336   | 336   |
| BOTTOM BRACKET DROP (I)        | 37    | 37    | 37    | 37    |
| CHAINSTAY (J)                  | 435   | 435   | 435   | 435   |
| WHEELBASE (K)                  | 1155  | 1175  | 1206  | 1229  |
| STANDOVER HEIGHT (L)           | 701   | 711   | 754   | 800   |
| FORK OFFSET (M)                | 51    | 51    | 51    | 51    |
| SEATPOST DIAMETER              | 30.9  | 30.9  | 30.9  | 30.9  |
| HANDLEBAR WIDTH                | 787   | 787   | 787   | 787   |
| STEM LENGTH                    | 35    | 35    | 35    | 35    |
| CRANK LENGTH                   | 170   | 175   | 175   | 175   |

All lengths in Millimeters